

# EDGE EX4DI

## 4" Suspended Direct/Indirect Linear

### Key Features

- 6063-T6 Extruded aluminum housing
- Highly reflective white painted reflector
- Room-Side Maintenance for LED system
- 5-year limited warranty covers LED, driver and fixture
- ETL Listed conforming to UL1598 in US and CSA 250 in Canada
- Approved for dry/damp location unless otherwise noted
- Maximum weight is 25 lbs. for a standard 4' fixture
- Buy American Act compliant



Example Part #: EX4DI-BW-HE-830HO-830-26'-AC48G1-U-OL1-1-0-W

<b>EX4DI</b>	<b>DIRECT SHIELDING</b>	<b>INDIRECT SHIELDING</b>	<b>DIRECT SOURCE</b>	<b>INDIRECT SOURCE</b>	<b>LENGTH OR PATTERN</b>	<b>MOUNTING</b>	<b>VOLTAGE</b>	<b>DRIVER</b>	<b>CIRCUITING</b>	<b>BATTERY &amp; EMERGENCY</b>	<b>FINISH</b>	<b>FIXTURE OPTIONS</b>	<b>CONTROLS</b>
--------------	-------------------------	---------------------------	----------------------	------------------------	--------------------------	-----------------	----------------	---------------	-------------------	--------------------------------	---------------	------------------------	-----------------

DIRECT SHIELDING	INDIRECT SHIELDING	DIRECT SOURCE <sup>1</sup>	INDIRECT SOURCE <sup>1</sup>
<b>A</b> - Satine Lens <b>AL</b> - Drop Lens <b>HE</b> - High Efficiency <b>BW</b> - Batwing <b>WHE</b> - Asymmetric <b>HED</b> - Descent <i>Shielding pg. 2</i>	<b>HE</b> - High Efficiency <b>BW</b> - Batwing <b>WHE</b> - Asymmetric <b>HEA</b> - Ascent <i>Shielding pg. 2</i>	<b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K (available as BIOS) <b>40</b> - 4000K (available as BIOS) <b>TW3</b> - Tunable White (Blanco 3) <b>CL</b> - Custom Lumens <b>CW</b> - Custom Watts <i>Lumen Output pg. 2-3</i>	<b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K <b>40</b> - 4000K <b>B</b> - BIOS <b>TW3</b> - Tunable White (Blanco 3) <b>CL</b> - Custom Lumens <b>CW</b> - Custom Watts <i>Lumen Output pg. 3-4</i>

LENGTH OR PATTERN <sup>2</sup>	MOUNTING <sup>3</sup>	VOLTAGE	DRIVER	CIRCUITING
<b>__</b> - Individual Fixture <b>__</b> - Continuous Row <b>L_x_</b> - L Shape <b>R_x_</b> - Rectangle <b>S_</b> - Square <b>U_x_x_</b> - U-Shape <b>T_x_</b> - T Shape <b>X_x_x_</b> - X Shape <b>M</b> - Mod Layout <i>Length and Pattern pg. 4</i>	<b>_AC_G_</b> - (M)AC to Grid <b>_AC_JB_</b> - (M)AC to J Box <b>_AC_ST_</b> - (M)AC to Structure <b>_AC5_G_</b> - 5" Non-Power Canopy <b>_AC5_JB_</b> - 5" Non-Power Canopy <b>_SQ_G_</b> - 5" Square Canopy <b>_SQ_JB_</b> - 5" Square Canopy <b>WA</b> - Wall Mount <i>Mounting pg. 5</i>	<b>U</b> - Universal (120 thru 277V) <b>1</b> - 120V <b>2</b> - 277V <b>3</b> - 347V <i>Voltage pg. 5</i>	<b>OL1</b> - Osram (10%, 0-10v, standard) <b>OL2</b> - Osram (1%, 0-10v) <b>OL3</b> - Osram 347v (10%, 0-10v) <b>EE1</b> - eldoLED ECOdrive (1%, 0-10v) <b>ES1</b> - eldoLED SOLOdrive (0%, 0-10v) <b>LH1</b> - Lutron Hi-lume (1%, EcoSystem) <b>L51</b> - Lutron 5-Series (5%, EcoSystem) <b>PL2</b> - Philips Xitanium (1%, 0-10v) <b>PS1</b> - Philips Xitanium (50%/100%) <b>ND</b> - Non-Dimming <i>Driver pg. 5</i>	<b>1</b> - Single Circuit <b>2</b> - Dual Circuit <b>M</b> - Multi Circuit <b>E</b> - Emergency (entire fixture) <b>N</b> - Night Light (entire fixture) <i>Circuiting pg. 6</i>


BATTERY & EMERGENCY <sup>4</sup>	FINISH	FIXTURE OPTIONS	CONTROLS <sup>5</sup>
<b>0</b> - None <b>PL</b> - Philips Bodine 10W <b>IL</b> - Iota 10W <b>G</b> - Philips Bodine GTD <i>Battery and Emergency pg. 6</i>	<b>W</b> - White <b>S</b> - Metallic Silver <b>BL</b> - Textured Black <b>BR</b> - Bronze <b>GR</b> - Graphite <b>CC</b> - Custom Color <i>Finish pg. 6</i>	<b>CC-C</b> - Custom Color Canopy <b>LMRA</b> - Adjustable MR16 (LED) <b>XLED</b> - Fixed Xicato LED <i>Fixture Options pg. 6</i>	<b>DLMFC</b> - Wattstopper DLM (wired) <b>NLTAIR_</b> - Acuity nLight AIR (wireless) <b>EASYS</b> - Philips EasySense (wireless) <b>SNSLM</b> - Osram Sensillum (wireless) <b>WVLX</b> - Eaton Wavelinx (wireless) <b>VDO</b> - Lutron Vive Sensor (wireless) <b>VRF</b> - Lutron Vive Connected (wireless) <b>ENL_</b> - Enlighted (wireless) <i>Controls pg. 7</i>

<sup>1</sup>When specifying SOURCE the first \_ is for specifying either **8** - 80CRI, **9** - 90CRI or **B** - Bios. The ending \_\_ are for specifying output, example **HO** - High Output. When specifying BIOS use **B** and then specify color temperature, either 3500K or 4000K, and output, example **B35HO** - BIOS 3500K High Output. See output charts for more information. <sup>2</sup>Individual fixtures come in 2', 3', 4', 5', 6', 7', & 8' lengths. Continuous row come in 1/8" increments. For Mod layouts, specify pattern shape and overall dimensions. Example: L6x4: L pattern that is 6'x4'. <sup>3</sup>Specify AC Cable: Standard single AC = AC or Movable AC = MAC; Specify AC length standard AC is 48"; Specify grid: G1=15/16", G9=9/16", GS=Screw Slot. Example: AC48G1. MAC option not available with HEA - Ascent Indirect shielding option. <sup>4</sup>Enter quantity for Battery and Emergency, Example 2PL. <sup>5</sup>Controls can only be used with Single Circuit (**1**) or Emergency Circuit (**E**). See Controls chart on page 7 for driver options and more information.


Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



## Direct Shielding



## Indirect Shielding



### Direct Source: White LED<sup>1</sup>

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory
- 80 CRI = R9≥19 and 90 CRI = R9≥61

### Custom Output - Lumens OR Wattage

<b>CL</b> _____	Specify CRI, CCT and desired lumens (i.e. CL835500)	Specify lumens between standard offering listed below. Lumens are specified per color temp
<b>CW</b> _____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Specify watts between standard offering listed below

### 80 CRI

	Color	Lumens per foot	Shielding <sup>1</sup>											
			A Satine		AL Drop		HE High Efficiency		BW Batwing		WHE Asymmetric		HED Descent	
			LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft
<b>830</b>	3000K	500	111	4.5	101	4.9	123	4.1	124	4.0	124	4.0	111	4.5
<b>830HO</b>	3000K	750	112	6.7	102	7.3	127	5.9	125	6.0	125	6.0	113	6.6
<b>830VHO</b>	3000K	1000	111	11.8	103	9.7	127	7.9	125	8.0	125	8.0	113	8.9
<b>835</b>	3500K	500	114	4.4	105	4.8	127	4.0	125	4.0	125	4.0	115	4.4
<b>835HO</b>	3500K	750	115	6.5	105	7.1	129	5.8	127	5.9	127	5.9	117	6.4
<b>835VHO</b>	3500K	1000	115	8.7	107	9.3	131	7.6	129	7.7	129	7.7	116	8.6
<b>840</b>	4000K	500	114	4.4	105	4.8	127	4.0	125	4.0	125	4.0	115	4.4
<b>840HO</b>	4000K	750	115	6.5	105	7.1	129	5.8	127	5.9	127	5.9	117	6.4
<b>840VHO</b>	4000K	1000	115	8.7	107	9.3	131	7.6	129	7.7	129	7.7	116	8.6

### 90 CRI

<b>927</b>	2700K	500	91	5.5	83	6.0	104	4.8	103	4.9	103	4.9	93	5.4
<b>927HO</b>	2700K	750	92	8.2	83	9.0	105	7.2	103	7.3	103	7.3	93	8.1
<b>930</b>	3000K	500	99	5.0	90	5.6	111	4.5	111	4.5	111	4.5	101	5.0
<b>930HO</b>	3000K	750	100	7.5	91	8.3	113	6.6	112	6.7	112	6.7	102	7.4
<b>935</b>	3500K	500	99	5.1	89	5.6	111	4.5	110	4.5	110	4.5	100	5.0
<b>935HO</b>	3500K	750	100	7.5	90	8.3	113	6.7	111	6.7	111	6.7	101	7.4
<b>940</b>	4000K	500	99	5.1	89	5.6	111	4.5	110	4.5	110	4.5	100	5.0
<b>940HO</b>	4000K	750	100	7.5	90	8.3	113	6.7	111	6.7	111	6.7	101	7.4

### Direct Source: BIOS<sup>1</sup>

- CRI >84, R9 >90
- Spectrum focused lighting for circadian stimulus
- High EML or M/P ratio: .8 for 3500K, .9 for 4000K
- High COI: >3.0
- Available for use with most Driver or Control options

### Custom Output - Lumens OR Wattage

<b>CLB</b> _____	Specify CRI, CCT and desired lumens (i.e. CL835500)	Specify lumens between standard offering listed below. Lumens are specified per color temp
<b>CWB</b> _____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Specify watts between standard offering listed below

### BIOS

	Color	Lumens per foot	Shielding <sup>1</sup>					
			A Satine		HE High Efficiency		BW Batwing	
			LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft
<b>B35</b>	3500K	500	69	7.2	82	6.1	80	6.2
<b>B35HO</b>	3500K	750	68	11.0	82	9.1	81	9.3
<b>B35VHO</b>	3500K	1000	N/A	N/A	79	12.6	N/A	N/A
<b>B40</b>	4000K	500	69	7.2	81	6.1	80	6.2
<b>B40HO</b>	4000K	750	68	11.0	82	9.1	81	9.3
<b>B40VHO</b>	4000K	1000	N/A	N/A	79	12.6	N/A	N/A

<sup>1</sup>LPW and watts/ft based off 48" fixture size.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Direct Source: Blanco<sup>1</sup>

- CRI >90, R9 >92
- 3 Channel tunable white for precise black body curve CCT
- Allows for high color consistency between fixtures

- Self-commissioning with Wattstopper DLM integrated controls
- Requires Control Ordering Code **B3LM** (pg. 6)
- Requires Drive Ordering Code **EC2** (pg. 4)

Blanco 3 Tunable White (TW3)

	Range	Shielding <sup>1</sup>		HE			BW			
		A Satine	LPW	Watts/ft	High Efficiency	LPW	Watts/ft	Batwing	LPW	Watts/ft
<b>TW3</b>	2700-6500K	635	74	8.6	720	84	8.6	712	83	8.6

<sup>1</sup>Lumens/ft LPW and watts/ft based off 48" fixture at full output at 4000K.

Indirect Source: White LED<sup>1</sup>

Custom Output - Lumens OR Wattage

<b>CL</b> _____	Specify CRI, CCT and desired lumens (i.e. CL835500)	Specify lumens between standard offering listed below. Lumens are specified per color temp
<b>CW</b> _____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Specify watts between standard offering listed below

80 CRI

	Color	Lumens per foot	Shielding <sup>1</sup>		BW		WHE		HEA	
			HE	High Efficiency	Batwing	Asymmetric	Ascent	LPW	Watts/ft	
			LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft	LPW	Watts/ft
<b>830</b>	3000K	500	132	3.8	121	4.1	106	4.7	126	4.0
<b>830HO</b>	3000K	750	135	5.6	122	6.1	108	7.0	128	5.8
<b>830VHO</b>	3000K	1000	137	7.3	122	8.2	110	109.9	131	7.7
<b>835</b>	3500K	500	136	3.7	122	4.1	109	4.6	130	3.8
<b>835HO</b>	3500K	750	141	5.3	126	5.9	110	6.8	133	5.7
<b>835VHO</b>	3500K	1000	141	7.1	126	7.9	110	9.1	135	7.4
<b>840</b>	4000K	500	136	3.7	122	4.1	109	4.6	130	3.8
<b>840HO</b>	4000K	750	141	5.3	126	5.9	110	6.8	133	5.7
<b>840VHO</b>	4000K	1000	141	7.1	126	7.9	110	9.1	135	7.4

90 CRI

<b>927</b>	2700K	500	111	4.5	101	5.0	87	5.7	106	4.7
<b>927HO</b>	2700K	750	112	6.7	102	7.4	88	8.5	108	7.0
<b>927VHO</b>	2700K	1000	112	8.9	103	9.7	N/A		110	9.1
<b>930</b>	3000K	500	120	4.2	109	4.6	96	5.2	114	4.4
<b>930HO</b>	3000K	750	121	6.2	109	6.9	96	7.8	116	6.4
<b>930VHO</b>	3000K	1000	121	8.2	109	9.2	N/A		116	8.6
<b>935</b>	3500K	500	120	4.2	109	4.6	96	5.2	114	4.4
<b>935HO</b>	3500K	750	121	6.2	110	6.8	95	7.9	116	6.5
<b>935VHO</b>	3500K	1000	121	8.3	109	9.2	N/A		115	8.7
<b>940</b>	4000K	500	120	4.2	109	4.6	96	5.2	114	4.4
<b>940HO</b>	4000K	750	121	6.2	110	6.8	95	7.9	116	6.5
<b>940VHO</b>	4000K	1000	121	8.3	109	9.2	N/A		115	8.7

Indirect Source: BIOS<sup>1</sup>

Custom Output - Lumens OR Wattage

<b>CLB</b> _____	Specify CRI, CCT and desired lumens (i.e. CL835500)	Specify lumens between standard offering listed below. Lumens are specified per color temp
<b>CWB</b> _____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Specify watts between standard offering listed below

BIOS

	Color	Lumens per foot	Shielding <sup>1</sup>	
			HE	High Efficiency
			LPW	Watts/ft
<b>B35</b>	3500K	500	87	5.7
<b>B35HO</b>	3500K	750	86	8.7
<b>B35VHO</b>	3500K	1000	85	11.7
<b>B40</b>	4000K	500	87	5.7
<b>B40HO</b>	4000K	750	86	8.7
<b>B40VHO</b>	4000K	1000	85	11.7

<sup>1</sup>LPW and watts/ft based off 48" fixture size.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed and Fabricated in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

EX4DI\_LED\_SPEC\_APRIL2019



## Indirect Source: Blanco <sup>1</sup>

### Blanco 3 Tunable White (TW3)

<b>TW3</b>	Range	Shielding <sup>1</sup>		
	2700-6500K	<b>HE</b> High Efficiency	Lumens/ft 783	LPW 92


<sup>1</sup>Lumens/ft LPW and watts/ft based off 48" fixture at full output at 4000K.

## Length

- For Continuous Runs, add 3/16" (4.7mm) for each end plate or 3/8" (9.5mm) to the overall length of the row
- BIOS and Blanco3 are only available in foot lengths







2	3	4	5	6	7	8	-
Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Cont. Run
24-3/8" (619.1mm)							Specify nominal overall row length to the 1/8" Longer lead-time may apply for lengths to the 1/8". Consult factory.
36-3/8" (934.8mm)							
	48-3/8" (1228.7mm)						
		60-3/8" (1533.5mm)					
			72-3/8" (1838.3mm)				
				84-3/8" (2143.1mm)			
					96-3/8" (2447.9mm)		
Specify to the 1/8" >>>							

## Pattern



- Specify pattern shape and overall dimensions (includes corner dimensions)
- Refer to dimensions table below for available standard lengths
- All connectors are direct only
- 90 degree horizontal corners are 12"x12" (overall, outside dimension)
- Angles and shapes not shown require Mod Pattern; consult factory
- Only available with "A" or "HE" lens options

S_	R_x_	U_x_x_	L_x_	T_x_	X_x_	M
Square Provide A Example: <b>S4'</b> Minimum Length-4'x4'	Rectangle Provide AxB Example: <b>R4'x4'</b> Minimum Length-4'x4'	U-Shape Provide AxBxC Example: <b>U3'x4'x3'</b> Minimum Length-3'x4'x3'	L-Shape Provide AxB Example: <b>L3'x3'</b> Minimum Length-3'x3'	T-Shape Provide AxB Example: <b>T3'x5'</b> Minimum Length-3'x5'	X-Shape Provide AxB Example: <b>X5'x5'</b> Minimum Length-5'x5'	Mod Layout For patterns or lengths not shown or standard



Horizontal Details: Every Connection is 12" x 12" in Overall Dimension

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.




## Mounting


- Specify cable length in ordering code (AC48G1)
- Standard specifiable lengths are 48", 120", 240" and 350"
- End plates and power cord attached at factory
- Aircraft cable (AC) mounts on 4' (1219.2mm) and 8' (2438.4mm) centers
- Maximum recommended movable mounting locations are 12" from end of 4' fixture and 18" from end of 8' fixture
- Aircraft Cable supplied with 5" (127mm) power and 2" (50.8mm) non-power canopies
- MAC options not available with HEA lens option

- Canopies are painted white unless otherwise specified
- Canopy color specified in fixture options section
- Approved for dry/damp location unless otherwise noted
- Refer to installation instructions during installation at the job site
- Maximum fixture weight is 25 lbs for a standard 4' fixture
- AC\_GS and MAC\_GS - works with screw slot and bolt slot grid ceiling types
- Wall Mount - ADA Compliant, bracket is 1/2" off wall
- MAC options not available with HEA lens option

AC_G1	Aircraft Cable 1" (15/16") T-Bar
AC_G9	Aircraft Cable 9/16" T-Bar
AC_GS	Aircraft Cable Screw Slot T-Bar
AC_JB	Aircraft Cable Junction Box
AC_ST	Aircraft Cable Structure
AC5_G	Aircraft Cable 5" (127mm) Non-Power Canopy
AC5_JB	Aircraft Cable 5" (127mm) Non-Power Canopy
SQ_G	Aircraft Cable 5" (127mm) Square Canopy
SQ_JB	Aircraft Cable 5" (127mm) Square Canopy
MAC_G1	Moveable AC 1" (15/16") T-Bar
MAC_G9	Moveable AC 9/16" T-Bar
MAC_GS	Moveable AC Screw Slot T-Bar
MAC_JB	Moveable AC Junction Box
MAC_ST	Moveable AC Structure
MAC5_G	Moveable AC 5" (127mm) Non-Power Canopy
MAC5_JB	Moveable AC 5" (127mm) Non-Power Canopy
MSQ_G	Moveable AC 5" (127mm) Square Canopy
MSQ_JB	Moveable AC 5" (127mm) Square Canopy
WA	Wall Mount



## Straight EDGE Joint System



- The Straight EDGE Joint comes standard for all runs.
- Two connection points - one to cinch fixtures together, the other to perfectly align all fixtures in a run.
- Factory-installed light shields on both sides of the fixture ensure no light leaks.
- Patent Pending.

## Voltage

- Some EX4DI configurations will not accommodate all voltage options; consult with factory

U	Universal
1	120 volt
2	277 volt
3	347 volt

## Driver

- Standard Driver Option = OL1
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more driver options see Pinnacle Resource Guide
- Some EX4DI configurations will not accommodate all driver options; consult with factory

OL1	Osram Optotronic 10%, 0-10v
OL2	Osram Optotronic 1%, 0-10v, nominal 1% dimming range
OL3	Osram Optotronic 347v 10%, 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
EE6	eldoLED ECOdrive 1%, for nLight Air Wireless
ES1	eldoLED SOLOdrive 0%, 0-10v Logarithmic
ES2	eldoLED SOLOdrive 0%, 0-10v Linear
ES6	eldoLED SOLOdrive 0%, for nLight Air Wireless
LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
L51	Lutron 5-Series 5%, EcoSystem, LDE5
PL2	Philips Advance Xitanium 1%, 0-10v
PS1	Philips Advance Xitanium Step Dimming 50%/100%
EC2	Constant Voltage LED driver, 120v or 277v required
ND	Non-Dimming

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed and Fabricated in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

EX4DI\_LED\_SPEC\_APRIL2019



## How to Specify Circuiting, Battery and Emergency

- 1**
- Select fixture circuiting from options below
  - Some EX4DI configurations will not accommodate all circuiting options, consult with factory

### Circuiting

<b>1</b>	Single Circuit
<b>2</b>	Dual Circuit
<b>M</b>	Multi Circuit
<b>E</b>	Emergency Circuit only
<b>N</b>	Night Light Circuit only

- 2** + **3**
- Battery and emergency section options are available in addition to fixture circuit
  - Select battery and emergency section options below; factory shop drawing required
  - Some EX4DI configurations will not accommodate all circuiting options, consult with factory

### Battery and/or Emergency If Required

<b>0</b>	No battery or specific emergency section required
----------	---

#### Battery

- Select battery section type if required, indicate total QTY. *Example 2PL*
- 90 minute battery runtime; test button location dependant on configuration, consult factory
- No battery option available for 2' or 3' lengths
- Entire direct fixture housing is on battery for lengths up to 5'
- Half of direct fixture is on battery for 6' or 8' housing lengths
- For more battery options available, see Pinnacle Resource Guide

#### For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 92.3 (LPW) x 10 (watts) = 923 battery lumen output

<b>0</b>	No battery
<b>_PL</b>	Philips Bodine 10w Integral
<b>_IL</b>	Iota 10w Integral

#### Battery OR Emergency Ordering Examples

- Single circuit, 10w Integral Battery      Ordering Code: 1-1PL
- Emergency only, 10w Integral Battery      Ordering Code: E-1PL
- Single circuit, GTD required      Ordering Code: 1-1G

#### Emergency

- Select emergency section type if required, indicate total QTY. *Example 1E*
- Combine battery and emergency section ordering codes if both options are selected

<b>_E</b>	Emergency circuit section
<b>_N</b>	Night Light circuit section
<b>_L</b>	Life Safety circuit section NO THROUGH WIRE
<b>_G</b>	Philips Bodine GTD, Generator Transfer Device section

#### Combination Section Ordering Examples

- Single circuit, (1) 10w battery, (1) emergency section      Ordering Code: 1-1PL1E
- Multi circuit, (2) 10w battery, (2) emergency sections      Ordering Code: M-2PL2E
- Single circuit, (1) night light section      Ordering Code: 1-1N

### Finish

- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

<b>W</b>	White
<b>S</b>	Metallic Silver
<b>BL</b>	Textured Black
<b>GR</b>	Graphite
<b>BR</b>	Bronze
<b>CC</b>	Custom Color

### Fixture Options

- Additional options to enhance the fixture and finish of the product
- Specify CC-C to match housing. If not specified, canopy will be standard matte white

<b>CC-C</b>	Custom Canopy Color
-------------	---------------------



## Controls

- Pinnacle Lighting offers easy to specify network control solutions that connect to an intelligent centralized system to maximize lighting energy efficiencies or integral sensors for individual fixture control
- Pinnacle Lighting fixtures ship technology ready; commissioning by others
- Controls can only be used with Single Circuit (1) or Emergency Circuit (E),
- Contact factory for any non-standard configurations for layout or placement
- One drop/sensor per run typical, contact factory for more information

	Solution	Components	Network/Sensor	Connection	Required Drivers	Limitations
<b>DLMFC</b>	Legrand Wattstopper DLM	LMFC-011	Digital Lighting Management (DLM)	Wired, one RJ45 ports	OL1, OL2, OL3	Not available with Battery
<b>NLTAIR</b>	Acuity nLight AIR Wireless Connected	RIO EZDL G2	nLight	Wireless	EE6, ES6	Not available with 347 volt
<b>NLTAIRS</b>	Acuity nLight AIR Wireless	RES7 G2	nLight, Daylight/PIR Occupancy	Wireless	EE6, ES6	
<b>NLTAIRM</b>	Acuity nLight AIR Wireless	RES7 PDT G2	nLight, Daylight/PIR Occupancy	Wireless	EE6, ES6	
<b>EASYS</b>	Philips EasySense	SNS-200	Daylight/PIR Occupancy	Wireless to switches	PR1	Not available with 347 volt
<b>SNSLM</b>	Osram Sensilum	EN-CLM-PIR-DD-ZB	Encelium, Daylight/PIR Occupancy	Wireless	OD1, OL1, OL2	Not available with 347 volt
<b>WLVX</b>	Eaton Wavelinx	SWPD1, NSP3IVMVDC1	WaveLinx WCL, Daylight	Wireless	OL1, OL2	Not available with 347 volt
<b>VDO</b>	Lutron Vive Sensor	DFCSJ-OEM-OCC	Vive, Daylight/PIR Occupancy	Wireless	OD1, PR1	Not available with 347 volt
<b>VRF</b>	Lutron Vive Connected	DFCSJ-OEM-RF	Vive	Wireless	OD1, PR1	Not available with 347 volt
<b>ENLI</b>	Enlighted	SU-5E-IOT, CU-4E	Enlighted, Daylight/PIR Occupancy	Wireless	OL1, OL2	Not available with 347 volt
<b>ENLC</b>	Enlighted	SU-5E-CL, CU-4E	Enlighted, Daylight/PIR Occupancy	Wireless	OL1, OLW	Not available with 347 volt

## Controls: Tunable White


- Pinnacle Lighting offers easy to specify tunable white solutions for integrated building control solutions or standalone controls
- Pinnacle Lighting fixtures ship technology ready; commissioning by others
- Controls can only be used with Single Circuit (1) or Emergency Circuit (E),
- Contact factory for any non-standard configurations for layout or placement

	Solution	Components	Network/Sensor	Connection	Required Drivers	Limitations
<b>B3LM</b>	Legrand Wattstopper Blanco 3	BLM3-DLM	Digital Lighting Management (DLM)	Wired, one RJ45 ports	EC2	Not available with 347 volt

## Photometrics

### Satine Lens - Open

Test # Scaled from ITL91451 & ITL91463  
 Catalog # EX4DI-BW-BW-840VHO-840VHO-4  
 Lumens 8000 lm  
 Watts 66.8 W  
 Efficacy 120 LPW



### Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	666	666	666	666	666
5	663	663	665	667	668
15	640	642	657	671	675
25	591	597	635	674	689
35	519	533	596	662	687
45	430	450	526	598	620
55	328	351	420	472	479
65	221	239	286	315	316
75	112	122	146	156	153
85	20	25	30	31	30
90	0	0	0	0	0
95	30	79	458	125	81
105	115	148	703	1127	877
115	211	228	528	1307	1527
125	267	308	527	1092	1284
135	298	353	562	904	1090
145	336	391	564	756	845
155	379	420	532	639	680
165	417	435	485	531	551
175	438	441	447	453	456
180	441	441	441	441	441

### Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	9427	11268	12871
55	8845	10990	12574
65	8104	10273	11358
75	6833	8760	9319
85	4334	6090	6364

For all available IES files, please visit our website at [pinnacle-ltg.com](http://pinnacle-ltg.com). Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP accredited testing laboratory. Testing conducted at 25°C ambient conditions.

Specifications and dimensions subject to change without notice. Specification sheets that appear on [pinnacle-ltg.com](http://pinnacle-ltg.com) are the most recent version and supersede all other previously printed or electronic versions.





## Applications & Certificates

**Construction:** 6063-T6 Extruded aluminum housing. Highly reflective steel white painted reflector.

**Shielding:** Diffuse snap-in acrylic lens, removable for maintenance.

**Mounting:** Aircraft cable and wall mount available. Select from 2 aircraft cable options. Select the straight aircraft cable that mounts on 4'-0" (1219.2mm) and 8'-0" (2438.4mm) centers or the moveable adjustable Y-cable mount. The Y-Cable design allows for adjustable mounting locations. Aircraft Cable supplied with 5" (127mm) power and 2" (50.8mm) non-power canopies. Refer to installation instructions for appropriate ceiling detail. Canopies are painted white unless otherwise specified. Maximum fixture weight is 20 lbs. for a standard 4' fixture.

**White LED:** 25°C test environment. Lumen output/wattage has a margin of +/- 5%; 2' or 3' lengths may have a greater wattage deviation. All luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. Lifetime Projection L70 = 146,500 hours and L90 = 45,000 hours. MacAdam 3-Step Ellipses. Not all products are Lighting Facts listed. For all available IES files, please visit our website at pinnacle-ltg.com. Three lumen packages available. Standard, High (HO) and Very High (VHO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 80 CRI = R9≥19 and 90 CRI = R9≥61.

**BIOS LED:** Spectrum focused lighting for circadian stimulus. EML or M/P ratio: .8 for 3500K, .9 for 4000K. COI >3.0. Not all lumen packages available. Three lumen packages available. Standard, High (HO) and Very High (VHO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page.

**Tunable White LED:** Blanco 3; 3 Channel tunable white for precise black body curve CCT. Self-commissioning with Wattstopper DLM integrated controls. Custom lumen output and color temperature configurations require use of controls.

**Voltage:** Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL3 in Driver section when 347 volt (3) is selected. Some EDGE configurations will not accommodate all voltage options; consult with factory.

**Driver:** Standard Driver Option is Osram 0-10V, 10% = OL1. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 94.3°F/34.6°C. For more driver options, see Pinnacle Resource Guide. Some EDGE configurations will not accommodate all driver options.

**Circuiting:** Select from single circuit (1), Multi circuit - For multiple circuiting and zone control, requires factory shop drawing (M), Emergency circuit (E), Life Safety (L) or Night Light circuit (N). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some EDGE configurations will not accommodate all circuiting options; consult with factory.

**Battery & Emergency:** Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button location dependant on configuration, consult factory. For more Battery options, see Pinnacle Resource Guide.

**Finish:** Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes or for additional custom color and finish options.

**Controls:** DLM utilizes wired network connections for digital control through switching and dimming. nLight Air rES7 sensor provides wireless control, daylight harvesting and occupancy detection with PIR using eldoLED LED drivers. nLight Air rES7 sensor provides wireless control, daylight harvesting and occupancy detection with PDT using eldoLED LED drivers. nLight Air rIO module provides wireless control using eldoLED LED drivers. EasySense sensor provides daylight harvesting and PIR occupancy detection using the SR LED driver; the Philips app provides advanced configurations. ENCELIUM SensiLUM sensor provides wireless control, daylight harvesting and PIR occupancy; driver data is available when using the DEXAL driver. ENCELIUM SensiLUM sensor provides wireless control, daylight harvesting and PIR occupancy; driver data is available when using the DEXAL driver. Wavelinx Connected Lighting sensor provides wireless control and daylight harvesting using 0-10V LED drivers. Lutron Vive sensor provides wireless control, daylight harvesting and PIR occupancy detection using DEXAL or SR LED drivers. Lutron Vive module provides wireless control using DEXAL or SR LED drivers. Enlighted Smart Sensor provides multi-functionality including daylight harvesting and PIR occupancy; for IOT platform using 0-10v LED drivers. Enlighted Smart Sensor provides multi-functionality including daylight harvesting and PIR occupancy; for Connected platform using 0-10v LED drivers.

**Labels:** ETL listed conforming to UL1598 and CSA 250. Standard, HO and VHO lumen packages are IC Rated, approved for dry/damp location unless otherwise noted.

**Fixture Weight:** Maximum fixture weight is 25lbs per 4' fixture.

**Buy American Act Compliant**

**Warranty:** EDGE LED offered with a 5-year limited warranty. Covers LED, driver and fixture.