


*Shown with SARI2 option



LiFT LF11D

1x1 Direct Recessed Architectural Square
with Sound Absorption



Key Features

- Formed 20 gauge cold rolled steel housing
- Highly reflective die-formed white painted reflector
- Fabricated, captive lens with 3 lens positions
- Sound Absorption available in specific configurations
- LiFT offered with a 5-year limited warranty. Covers LED, driver and fixture
- ETL Listed conforming to UL1598 in US and CSA 250 in Canada
- Maximum fixture weight is 12 lbs
- Room-Side Maintenance for LED system
- Buy American Act compliant
- Apparent Noise Reduction Coefficient (NRC) is up to 1.5



Example Part #: LF11D-A-830HO-GF-U-PL2-1-0-W

LF11D - SHIELDING - CRI, CCT & OUTPUT - MOUNTING - VOLTAGE - DRIVER - CIRCUITING - BATTERY & EMERGENCY - FINISH - FIXTURE OPTIONS

| --- | ----- | ----- | --- |
|---|--|---|--|
| SHIELDING ¹ | SOURCE ² | MOUNTING | VOLTAGE |
| A - Flush Satine Lens AL - Drop Satine Lens AR - Regress Satine Lens ASF - Acoustic Solution Flush <i>(use P__ to specify color)</i> ASR - Acoustic Solution Regress <i>(use P__ to specify color)</i> <i>Shielding pg. 2</i> | 27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K CL - Custom Lumens CW - Custom Watts NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Source pg. 3</i> | G - Grid Ceiling <i>(Fixture does not fit in standard grid spacing)</i> GF - Grid Ceiling with Flange FL - Flanged SF - Spackle Flange <i>Mounting pg. 4</i> | U - Universal <i>(120 thru 277V)</i> 1 - 120V 2 - 277V 3 - 347V NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Voltage pg. 4</i> |

| --- | --- | --- | --- |
|--|--|---|---|
| DRIVER | CIRCUITING | BATTERY & EMERGENCY | FINISH |
| FSD - Factory Select Driver <i>(1%, 0-10v)</i> PL2 - Advance Xitanium <i>(1%, 0-10v, standard)</i> EE1 - eldoLED ECODrive <i>(1%, 0-10v)</i> ES1 - eldoLED SOLOdrive <i>(0%, 0-10v)</i> LH1 - Lutron Hi-Lume <i>(1%, EcoSystem)</i> OL2 - Osram Optotronic <i>(1%, 0-10v)</i> OL4 - Osram Optotronic 347v <i>(1%, 0-10v)</i> NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Driver pg. 5</i> | 1 - Single Circuit E - Emergency <i>(entire fixture)</i> N - Night Light <i>(entire fixture)</i> NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Circuiting pg. 5</i> | 0 - None 1PB - Bodine 10W FSG - Factory Select ALCR GI - Iota ETS DR GB - Bodine GTD NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Battery and Emergency pg. 5</i> | W - White S - Metallic Silver BL - Textured Black BR - Bronze GR - Graphite CC - Custom Color <i>Finish pg. 5</i> |

| --- | --- |
|---|---|
| FIXTURE OPTIONS | CONTROLS ³ |
| CP - Chicago Plenum AM - Antimicrobial Paint FW6 - 6' Flex Whip GMF - Slow Blow Fusing NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Fixture Options pg. 5</i> | DLMFC - Wattstopper DLM <i>(wired)</i> ENLI - Enlighted IOT <i>(remote)</i> ENLC - Enlighted Connected Lighting <i>(remote)</i> NA - Not Applicable <i>(for specifying SA fixtures)</i> <i>Controls pg. 6</i> |

¹When specifying a fixture with Sound Absorption (no lit components), use NA for the following sections of the part number: SOURCE, VOLTAGE, DRIVER, CIRCUITING, BATTERY & EMERGENCY, or CONTROLS.
²When specifying SOURCE the first _ is for specifying either 8 - 80CRI, 9 - 90CRI. The ending __ are for specifying output, example HO - High Output. See output charts for more information. ³Controls can only be used with Single Circuit (1) or Emergency Circuit (E). See Controls chart on page 5 for driver options and more information.




Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Shielding

- Fabricated, captive lens with 3 lens positions
- Highly reflective white reflectors maintain uniform lens brightness






Ordering Code

| A or ASF | AL | AR or ASR |
|---|---|--|
| Flush Satine Lens or Acoustic Solution | Drop Satine Lens | Regress Satine Lens or Acoustic Solution |
|  |  |  |

Acoustic Solutions

- 9mm PET Polyester Fiber acoustic panel
- Recyclable and contains up-to 90% post-consumer content
- Use SAFP__ or SARP__ for direct panels
- Colors below are for representation purposes, color may vary from photograph, contact factory for sample.
- Specify the color of the Sound Absorption with the numeric code below in the Shielding portion of the part number. For example, SAFP04 for Direct Sound Absorption, Flush Mounting, White 04.

Standard Colors

| P04 - White | P12 - Medium Grey | P27 - Black | P28 - Dark Grey | P33 - Royal Blue |
|--|---|---|--|---|
|  |  |  |  |  |

Secondary Colors - May increase lead-time for order. Consult Factory.

| P02 - Yellow | P03 - Orange | P05 - Light Tan | P06 - Carmel | P10 - Silver | P11 - Light Grey | P13 - Granny Smith |
|--|---|---|---|--|---|---|
|  |  |  |  |  |  |  |
| P14 - Lime | P16 - Dark Blue | P17 - Red | P18 - Dark Red | P19 - Purple | P22 - Sky Blue | P23 - Deep Blue |
|  |  |  |  |  |  |  |
| P25 - Grey | P26 - Heathered Grey | P34 - Teal | P36 - Dark Silver | P37 - Blue | PCC - Custom Color | |
|  |  |  |  |  | Please note there is a minimum order quantity for custom matching. Consult factory for order quantity, price and lead-time. | |



Source: White LED

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory
- 80 CRI = R9≥19 and 90 CRI = R9≥61

Sound Absorption

NA Not applicable (for Sound Absorption fixtures)

Custom Output- Lumens OR Wattage

CL Specify CRI, CCT and desired lumens (i.e. CL8352000) Specify lumens between standard offering listed below. Lumens are specified per color temp

CW Specify CRI, CCT and desired wattage (i.e. CW94020) Specify watts between standard offering listed below

80 CRI

| | Color | Lumens | Shielding A, AL, AR Satine Lens Watts | LPW |
|--------------|-------|--------|--|-----|
| 830LO | 3000K | 552 | 6.0 | 92 |
| 830MO | 3000K | 888 | 9.1 | 98 |
| 830HO | 3000K | 1215 | 12.8 | 95 |
| 835LO | 3500K | 571 | 6.0 | 95 |
| 835MO | 3500K | 931 | 9.1 | 102 |
| 835HO | 3500K | 1291 | 12.8 | 101 |
| 840LO | 4000K | 599 | 6.0 | 99 |
| 840MO | 4000K | 965 | 9.1 | 106 |
| 840HO | 4000K | 1329 | 12.9 | 103 |









90 CRI

| | | | | |
|--------------|-------|------|------|----|
| 927LO | 2700K | 448 | 6.0 | 74 |
| 927MO | 2700K | 722 | 9.1 | 79 |
| 927HO | 2700K | 991 | 12.8 | 77 |
| 930LO | 3000K | 478 | 6.0 | 79 |
| 930MO | 3000K | 771 | 9.1 | 85 |
| 930HO | 3000K | 1060 | 12.8 | 83 |
| 935LO | 3500K | 478 | 6.0 | 79 |
| 935MO | 3500K | 771 | 9.1 | 85 |
| 935HO | 3500K | 1060 | 12.8 | 83 |
| 940LO | 4000K | 503 | 6.0 | 84 |
| 940MO | 4000K | 810 | 9.1 | 89 |
| 940HO | 4000K | 1110 | 12.9 | 86 |




Mounting

- LiFT 1x1 Recessed does not fit into standard 1' x 1' grid spacing, see installs for grid mounting details.
- Designed to install into acoustical grid and inaccessible ceilings
- Grid retention clips integral to housing and require mechanical attachment
- Tie off fixture to structure with retention wires
- Maximum fixture weight is 12 lbs
- Refer to installation instructions during installation at the job site
- Approved for dry/damp location unless otherwise noted

| G | | GF | | FL |
|---|--|---|--|---|
| 1" Grid Mount <i>Does not fit into standard 1' grid spacing, see installs for grid mounting details.</i> <i>Works with 15/16" grid ceiling types.</i> <i>See profile for fixture position in relation to ceiling grid and tile.</i> | | 1/2" Flange <i>Utilize for Center of Tile Mounting.</i> <i>Fixture provided with Grid Spanning Bracket.</i> | | Flange <i>Utilize in drywall application when a flange is required.</i> |
| 9/16" Grid Mount <i>Does not fit into standard 1' grid spacing, see installs for grid mounting details.</i> <i>Works with 9/16" grid ceiling type. For regular tile installations, fixture position will be flush to the bottom of the tile.</i> | | Screw Slot Mounting <i>Does not fit into standard 1' grid spacing, see installs for grid mounting details.</i> <i>Works with screw slot and bolt slot ceiling types.</i> | | |
|  <p>Standard Tile</p> | |  <p>Standard Tile</p> | |  |
|  <p>Tegular Tile</p> | |  <p>Tegular Tile</p> | | SF Spackle Flange <i>Utilize in drywall application when a flangeless look is required.</i> |
|  <p>Standard Tile</p> | | | |  |
|  <p>Tegular Tile</p> | | | | |


G vs. GF Installation

LiFT 1x1 can be ordered as either Grid Ceiling Flange (G) or 1/2" Flange (GF). The 1/2" flange (GF) is for mounting the fixture in the center of a tile. The grid ceiling flange (G) is for if you are making a pattern with LiFT and would want to mount this off center. The GF mounting option comes with a grid spanning bracket (as show to the side) that will hold the fixture in the center of the tile.



Side-by-Side Installation

LiFT has the ability to have 2 fixtures mounted side by side using the same grid. This detail allows LiFT to be installed in a pattern with only the space of the T-bar between the fixtures.



Voltage

- Some LiFT configurations will not accommodate all voltage options; consult with factory

| | |
|-----------|--|
| U | Universal |
| 1 | 120 volt |
| 2 | 277 volt |
| 3 | 347 volt |
| NA | Not applicable (for Sound Absorption fixtures) |

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

LF11D_RECESSED_SPEC_MAY2022



Driver

- Standard Driver Option = PL2
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more Driver options, see Pinnacle Resource Guide on download pages at pinnacle-ltg.com
- Some LIFT configurations will not accommodate all driver options; consult with factory

0-10V Drivers

| | |
|------------|---|
| FSD | Factory Select Driver 1%, 0-10v |
| OL2 | Osram Optotronic, 1%, 0-10v |
| OL4 | Osram Optotronic 347v, 1% 0-10v, requires 347v option |
| EE1 | eldoLED ECOdrive 1%, 0-10v Logarithmic |
| EE2 | eldoLED ECOdrive 1%, 0-10v Linear |
| ES1 | eldoLED SOLOdrive 0-10v, 0% Logarithmic |
| ES2 | eldoLED SOLOdrive 0-10v, 0% Linear |

DALI Drivers

| | |
|------------|---|
| EE3 | eldoLED SOLOdrive .1%, DALI (logarithmic) |
| EE4 | eldoLED SOLOdrive .1%, DALI (linear) |

Lutron Drivers

| | |
|------------|---|
| LH1 | Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1 |
| LH4 | Lutron Hi-Lume 1%, 2-wire, Lutron-LTEA2W, 120v only |

Circuiting

- Select fixture circuiting from options below
- Some LIFT configurations will not accommodate all circuiting options; consult with factory

| | |
|-----------|--|
| 1 | Single Circuit |
| E | Emergency Circuit only |
| N | Night Light Circuit only |
| NA | Not applicable (for Sound Absorption fixtures) |

Battery & Emergency

- Select battery or emergency options if required
- Battery duration is 90 minutes
- Test button is integral
- For more Battery options, see Pinnacle Resource Guide on download pages at pinnacle-ltg.com

| | |
|-------------|---|
| 0 | No Battery |
| 1IRC | Iota 10w Remote |
| 1PB | Bodine 10w Integral |
| 1PRS | Bodine 7w Remote, Self Testing |
| 1PRD | Bodine 10w Remote, Dual Flex |
| FSG | Factory Select Automatic Load Control Relay (ALCR) |
| GI | Emergency Transfer Switch (ETS) DR Emergency Control Device |
| GB | Bodine GTD, Generator Transfer Device |

Battery & Emergency Ordering Examples

- Single circuit, 10w integral battery Ordering Code: 1-1PB
- Emergency circuit only, 10w integral battery Ordering Code: E-1PB

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 10 (watts) x 92.3 (LPW) = 923 battery lumen output

Finish

- Powder-coat white painted finish on exposed trim
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

| | |
|-----------|---|
| W | White (<i>white cord/white canopy</i>) |
| S | Metallic Silver (<i>grey cord/silver canopy</i>) |
| BL | Textured Black (<i>black cord/black canopy</i>) |
| BR | Bronze (<i>white cord/bronze canopy</i>) |
| GR | Graphite (<i>white cord/graphite canopy</i>) |
| CC | Custom Color (<i>white cord/color match canopy</i>) |

Fixture Options

- Additional options to enhance the fixture and finish of the product

| | |
|------------|--|
| CP | Chicago Plenum |
| AM | Antimicrobial Paint |
| FW6 | Flex Whip 6' |
| GMF | Internal Slow Blow Fuse |
| NA | Not applicable (for Sound Absorption fixtures) |

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

LF11D_RECESSED_SPEC_MAY2022



Controls

- Pinnacle Lighting offers easy to specify network control solutions that connect to an intelligent centralized system to maximize lighting energy efficiencies or integral sensors for individual fixture control
- Pinnacle Lighting fixtures ship technology ready; commissioning by others
- Controls can only be used with Single Circuit (1) or Emergency Circuit (E)
- Contact factory for any non-standard configurations for layout, placement, or EM options
- One sensor per housing typical, contact factory for more information

| | Solution | Components | Network/Sensor | Connection | RQD Drivers | Limitation |
|--------------|--|------------|-----------------------------------|-----------------------|-------------|-----------------------------|
| DLMFC | Legrand Wattstopper DLM | LMFC-011 | Digital Lighting Management (DLM) | Wired, two RJ45 ports | OL2, OL4 | None |
| ENLI | Enlighted IOT | CU-4E | Enlighted, Daylight/PIR Occupancy | Enlighted Cable | Any 0-10v | Not available with 347 volt |
| ENLC | Enlighted Connected Lighting | CU-4E | Enlighted, Daylight/PIR Occupancy | Enlighted Cable | Any 0-10v | Not available with 347 volt |
| NA | Not applicable (for Sound Absorption fixtures) | | | | | |

Approvals & Certifications

Construction: Formed 20 gauge cold rolled steel housing. Highly reflective die-formed white painted reflector. Wiring access available on top of housing. Lens is removable for room-side maintenance of lens, driver and LED boards.

Shielding: Single piece fabricated diffuse acrylic lens creating a fully luminous fixture.

Acoustic Solutions: Acoustic Solutions panels may be specified in place of lit fixture components to aid in Acoustic Control within a space. Acoustic Solutions material is a 9mm PET Polyester Fiber acoustic panel, containing up to 90% post-consumer content, made by others. Acoustic testing was completed by Riverbank Acoustical Laboratories. For specific reports, contact Pinnacle directly.

Mounting: LiFT 1x1 Recessed does not fit into standard 1' x 1' grid spacing, see installs for grid mounting details. Specify G for acoustical grid ceiling. Specify FL or SF for inaccessible ceilings. Grid retention clips integral to housing and require mechanical attachment. Tie off fixture to structure with retention wires. Maximum fixture weight is 12 lbs.

LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. All luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 146,500 hours and L90 = 45,000 hours. MacAdam 3-Step Ellipses. Not all products are Lighting Facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

Color & Lumen Output: Three lumen packages available. Low (LO), Middle (MO) and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 80 CRI = R9≥19 and 90 CRI = R9≥61.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL4 in Driver section when 347 volt (3) is selected. Some LiFT configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Advance 0-10V, 1% = PL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. For more driver options, see Pinnacle Resource Guide on download pages on pinnacle-ltg.com. Some LiFT configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). Some LiFT configurations will not accommodate all circuiting options; consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is remote. For more Battery options, see Pinnacle Resource Guide on download pages at pinnacle-ltg.com.

Finish: Powder-coat white painted finish on exposed trim.

Controls: DLM utilizes wired network connections for digital control through switching and dimming with 0-10v LED drivers. Enlighted Smart Sensor provides multi-functionality including daylight harvesting and PIR occupancy; for IOT platform using 0-10v LED drivers. Enlighted Smart Sensor provides multi-functionality including daylight harvesting and PIR occupancy; for Connected platform using 0-10v LED drivers.

Labels: ETL Listed conforming to UL1598 in US and CSA 250 in Canada. LO, MO, and HO lumen packages are IC Rated, approved for dry/damp location unless otherwise noted.

Fixture Weight: 12 lbs maximum.

Buy American Act Compliant

Warranty: LiFT LED offered with a 5-year limited warranty. Covers LED, driver and fixture.