


# LUCEN LU22

## 2x2 Architectural Recessed



### Key Features

- Boards and driver are specifically for Indigo Clean®
- Indigo Clean® is safe and effective at killing SARS-CoV-2, Influenza-A, Staph Aureus and a list of pathogens that negatively impact health
- Standard, white luminaire that provides on-demand disinfection when light is on
- Laboratory-tested disinfection
- Unlike UV disinfection, light is safe for occupants
- Proven effectiveness per independent lab test results
- Provides a cleaner, safer environment, even in areas normal cleaning doesn't reach



Example Part #: LU22-A-IC37-G1-U-ND-1-0-W



SHIELDING	CRI, CCT & OUTPUT	MOUNTING	VOLTAGE
<b>A</b> - Satine Lens	<b>IC32</b> - Indigo Clean LED, 3200K <b>IC37</b> - Indigo Clean LED, 3700K <b>IC43</b> - Indigo Clean LED, 4300K <i>Lumen Output pg. 2</i>	<b>G1</b> - 15/16" Grid <b>G9</b> - 9/16" Grid <b>GS</b> - Screw Slot Grid <b>FL</b> - Flanged <b>S</b> - Surface Mount <i>Mounting pg. 2</i>	<b>U</b> - Universal (120 thru 277V) <b>1</b> - 120V <b>2</b> - 277V <i>Voltage pg. 3</i>

DRIVER <sup>1</sup>	CIRCUITING	BATTERY & EMERGENCY	FINISH
<b>FSD</b> - Factory Select Driver (1%, 0-10v) <b>PL2</b> - Advance Xitanium (1%, 0-10v) <b>OL2</b> - Osram Optotronic (10%, 0-10v) <i>Driver pg. 3</i>	<b>1</b> - Single Circuit <b>E</b> - Emergency ( <i>entire fixture</i> ) <b>N</b> - Night Light ( <i>entire fixture</i> ) <i>Circuiting pg. 3</i>	<b>0</b> - None <b>1P</b> - Bodine 10W <b>1IC</b> - Iota 10W, CEC Listed <b>1G</b> - Bodine GTD <i>Battery and Emergency pg. 3</i>	<b>W</b> - White <i>Finish pg. 3</i>

FIXTURE OPTIONS <sup>2</sup>	CONTROLS
<b>TW</b> - Through-wiring <b>CP</b> - Chicago Plenum <b>AM</b> - Antimicrobial Paint <b>FW6</b> - 6' Flex Whip <b>GMF</b> - Slow Blow Fusing <b>PAF</b> - Paint After Fabrication <i>Fixture Options pg. 3</i>	<i>Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.</i>

<sup>1</sup> While we do offer dimmable driver options, please note that dimming is not recommended with Indigo-Clean fixtures as it can reduce the efficiency of disinfection. <sup>2</sup> Flex Whip (**FW6**) option not available with Chicago Plenum (**CP**) option.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



## Output

- 80 CRI R9 ≥ 23

## Indigo Clean LED

	Color	Watts	Shielding A	
			Satine Lens Lumens	LPW
IC32	3200K	30.4	2522	83
IC37	3700K	30.4	2587	85.1
IC43	4300K	30.5	2646	86.8

## Mounting

- LUCEN is offered with a universal flange for all grid types. See below for fixture placement in relation to the tile for each grid type
- Grid retention clips integral to housing and require mechanical attachment
- Tie off fixture to structure with retention wires
- Refer to installation instructions during installation at the jobsite
- Approved for dry/damp location when PAF is specified
- Maximum fixture weight is 15lbs - Surface Mount Box adds 10 lbs

G1	G9	GS	FL	S
<p><b>1" Grid Mount</b> Works with 15/16" grid ceiling types. See profile for fixture position in relation to ceiling grid and tile.</p>	<p><b>9/16" Grid Mount</b> Works with 9/16" grid ceiling type. For tegular tile installations, fixture position will not be flush to the bottom of the tile. See tegular tile profile image below.</p>	<p><b>Screw Slot Mounting</b> Works with screw slot and bolt slot grid ceiling types.</p>	<p><b>Flange Kit</b> A separate flange kit is supplied for installations into inaccessible or drywall applications. Flange kit ships from factory uninstalled separately from fixture.</p>	<p><b>Surface Mount</b> Utilize for hard lid ceiling applications. The 20 gauge steel frame easily secures to ceiling. Surface Mount Box adds 10 lbs</p>
<p>Standard Tile</p>	<p>Standard Tile</p>	<p>Tegular Tile</p>		<p>4-5/8" (117.6mm)</p>
<p>Tegular Tile</p>	<p>Tegular Tile</p>			



## Voltage

- Some LUCEN configurations will not accommodate all voltage options; consult with factory

<b>U</b>	Universal
<b>1</b>	120 volt
<b>2</b>	277 volt

## Driver

- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more Driver options, see Pinnacle Resource Guide
- Some LUCEN configurations will not accommodate all driver options; consult with factory

### 0-10V Drivers

<b>FSD</b>	Factory Select Driver 1%, 0-10v
<b>PL2</b>	Advance Xitanium 1%, 0-10v
<b>OL2</b>	Osram Optotronic, 1%, 0-10v

## Circuiting

- Select fixture circuiting from options below
- Some LUCEN configurations will not accommodate all circuiting options; consult with factory

<b>1</b>	Single Circuit
<b>E</b>	Emergency Circuit only (uses nIO EZ PH ER with NLIGHT)
<b>N</b>	Night Light Circuit only

## Battery & Emergency

- Select battery or emergency options if required
- Battery duration is 90 minutes
- Test button is integral to fixture
- For more Battery options, see Pinnacle Resource Guide

<b>0</b>	No Battery
<b>1IC</b>	Iota 10w Integral
<b>1P</b>	Bodine 10w Integral
<b>FSG</b>	Factory Select Automatic Load Control Relay (ALCR)
<b>GI</b>	Emergency Transfer Switch (ETS) DR Emergency Control Device
<b>GB</b>	Bodine GTD, Generator Transfer Device

### For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 10 (watts) x 92.3 (LPW) = 923 battery lumen output

### Battery & Emergency Ordering Examples

- Single circuit, 10w integral battery      Ordering Code: 1-1P
- Emergency circuit only, 10w integral battery      Ordering Code: E-1P

## Finish

- Powder-coat white painted finish on exposed trim

<b>W</b>	White
----------	-------

## Fixture Options

- Additional options to enhance the fixture and finish of the product

<b>TW</b>	Through-Wiring
<b>CP</b>	Chicago Plenum
<b>AM</b>	Antimicrobial Paint
<b>FW6</b>	Flex Whip 6'
<b>GMF</b>	Internal Slow Blow Fuse
<b>PAF</b>	Paint after fabrication

## Controls

- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568


LU22\_LED\_SPEC\_MAY2022



## Photometrics

### Satine Lens

Test # ITL93379  
 Catalog # LU22A-IC43  
 Lumens 2646 lm  
 Watts 30.5 W  
 Efficacy 86.8 LPW



### Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	979	979	979	979	979
5	973	973	972	972	971
10	956	956	955	953	953
15	929	927	926	925	924
20	891	889	887	885	884
25	843	842	840	838	838
30	788	788	787	787	786
35	727	727	729	731	733
40	661	663	666	673	675
45	590	594	601	612	616
50	520	524	535	548	554
55	446	453	464	479	485
60	372	381	395	411	415
65	297	307	324	339	346
70	223	235	253	268	275
75	150	165	183	198	204
80	85	100	117	129	134
85	31	42	53	59	61
90	0	0	0	0	0

### Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	2670	2719	2787
55	2488	2588	2705
65	2248	2453	2619
75	1854	2262	2522
85	1138	1946	2239

For all available IES files, please visit our website at [pinnacle-ltg.com](http://pinnacle-ltg.com). Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP accredited testing laboratory. Testing conducted at 25°C ambient conditions

## Approvals & Certifications

**Construction:** Formed 20 gauge cold rolled steel housing. Highly reflective die-formed white painted reflector. Wiring access available on top of housing. Captive and hinged center lens swings open for room-side maintenance of lens, driver and LED boards.

**Shielding:** Co-extruded acrylic lens with ribbed side channels evenly illuminates the side reflector giving the appearance of a fully luminous aperture. Available with standard satine lens or optional clear lens with linear slot or round perf insert.

**Mounting:** Designed to install into acoustical grid and inaccessible ceilings. Specify G1, G9 or GS for acoustical grid ceiling. Specify FL for inaccessible ceilings. Grid retention clips integral to housing and require mechanical attachment. Tie off fixture to structure with retention wires. Maximum fixture weight is 28 lbs

**Indigo Clean LED:** Spectrum focused lighting for continuous environmental disinfection. 25°C test environment. Lumen output/wattage has a margin of +/- 5%. All luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 80,000 hours. MacAdam 3-Step Ellipses. Not all products are lighting facts listed. For all available IES files, please visit our website at [pinnacle-ltg.com](http://pinnacle-ltg.com).

**Output:** One lumen package available. 80 CRI is available for 3700K and 4300K. 80 CRI = R9≥23.

**Voltage:** Universal (U), 120 volt (1) and 277 volt (2). Some LUCEN configurations will not accommodate all voltage options; consult with factory.

**Driver:** Standard Driver Option is Advance Xitanium 0-10v, 1% = PL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient oper-

ating conditions. Ambient operating range: -20°F/-30°C to 106°F/41°C. For more driver options, see Pinnacle Resource Guide. Some LUCEN configurations will not accommodate all driver options.

**Circuiting:** Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). Some LUCEN configurations will not accommodate all circuiting options, consult with factory.

**Battery & Emergency:** Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is integral to fixture.

**Finish:** Powder-coat white painted finish on exposed trim.

**Controls:** Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

**Labels:** UL and cUL Listed. Approved for dry/damp location unless otherwise noted. For damp location, must specify Paint After Fabrication (PAF) in the Options section of the luminaire.

**Fixture Weight:** 15 lbs maximum - Surface Mount Box adds 10 lbs.

**Buy American Act Compliant**

**Warranty:** LUCEN LED offered with a 5-year limited warranty. Covers LED, driver and fixture.