




LUCEN LU22

2x2 Architectural Recessed



Key Features

- Pre-painted formed 22 gauge cold rolled steel housing
- Highly reflective die-formed white painted reflector
- Wiring access available on both ends and top of housing
- LED offered with a 5-year limited warranty. Covers LED, driver and fixture
- UL and cUL Listed, LO, MO, and HO lumen packages are IC Rated
- Pre-painted fixtures are to be used in dry locations only
- For damp location, must specify Paint After Fabrication (PAF) in the Options section of the luminaire specification
- Maximum fixture weight is 15 lbs - Surface Mount Box adds 10 lbs
- Room-Side Maintenance for LED system
- Buy American Act compliant
- Indigo-Clean available, see Indigo-Clean specification sheets for details



Example Part #: LU22-A-830HO-G1-U-OL2-1-0-W

LU22 - SHIELDING - CRI, CCT & OUTPUT - MOUNTING - VOLTAGE - DRIVER - CIRCUITING - BATTERY & EMERGENCY - FINISH - FIXTURE OPTIONS - CONTROLS

SHIELDING	SOURCE ^{QS} 1	MOUNTING	VOLTAGE
A - Satine Lens ^{QS} W - White Rails ^{QS} S - Silver Rails ^{QS} <i>Shielding pg. 2</i>	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K CL - Custom Lumens CW - Custom Watts MOD - Mod options available <i>Lumen Output pg. 2</i>	G1 - 15/16" Grid ^{QS} G9 - 9/16" Grid ^{QS} GS - Screw Slot Grid ^{QS} FL - Flanged S - Surface Mount <i>Mounting pg. 3</i>	U - Universal (120 thru 277V) ^{QS} 1 - 120V ^{QS} 2 - 277V ^{QS} 3 - 347V <i>Voltage pg. 3</i>

DRIVER	CIRCUITING	BATTERY & EMERGENCY	FINISH
FSD - Factory Select Driver (1%, 0-10V) ^{QS} PL2 - Advance Xitanium (1%, 0-10V) ^{QS} OL4 - Osram 347V (1%, 0-10V) EE1 - eldoLED ECODrive (1%, 0-10V) ES1 - eldoLED SOLOdrive (0.1%, 0-10V) LH1 - Lutron Hi-lume (1%, EcoSystem) PR1 - Advance Xitanium SR OL2 - Osram (1%, 0-10V) ^{QS} MOD - Mod options available <i>Driver pg. 4</i>	1 - Single Circuit ^{QS} E - Emergency (entire fixture) ^{QS} N - Night Light (entire fixture) ^{QS} <i>Circuiting pg. 4</i>	0 - None ^{QS} 1P - Bodine 10W ^{QS} 1IC - Iota 10W, CEC Listed ^{QS} 1G - Bodine GTD FSG - Factory Select ALCR FSB - Factory Select Battery GI - Iota ETS DR GB - Bodine GTD <i>Battery and Emergency pg. 4</i>	W - White ^{QS} MOD - Mod options available <i>Finish pg. 5</i>

FIXTURE OPTIONS ²	CONTROLS ³
QS - QuickShip ^{QS} TW - Through-wiring CP - Chicago Plenum ^{QS} AM - Antimicrobial Paint FW6 - 6' Flex Whip ^{QS} GLR - Fast Blow Fusing ^{QS} GMF - Slow Blow Fusing PAF - Paint after fabrication MOD - Mod options available <i>Fixture Options pg. 5</i>	DLMFC - Wattstopper DLM (wired) DLMFS - Wattstopper LLLC (wireless) EASYS - Philips EasySense (wireless) SNSLM - Encelium Sensilum (wireless) WVLX - Eaton WaveLinx (wireless) VDO - Lutron Vive Sensor (wireless) VRF - Lutron Vive Connected (wireless) ENL - Enlighted, "C" Connected Lighting or "I" IOT ENL2 - Enlighted 2-Wire, "C" Connected Lighting or "I" IOT MOD - Mod options available <i>Controls pg. 6</i>

¹When specifying SOURCE the first _ is for specifying either 8 - 80CRI, 9 - 90CRI or B - BIOS. The ending _ _ are for specifying output, example HO - High Output. When specifying BIOS use B and then specify color temperature, either 3500K or 4000K, and output, example B35HO - BIOS 3500K High Output. See output charts for more information. BIOS dynamic available, please contact factory for more information. ²If specifying QS, QS must be used in fixture options section of part number to qualify. ³Controls can only be used with Single Circuit (1) or Emergency Circuit (E). See Controls chart on page 5 for driver options and more information



Shielding

- Single piece extruded diffuse lens with convex wings and articulated center spine
- Fully luminous housing with optimal glare control
- Highly reflective white reflectors maintain uniform lens brightness

Ordering Code

A	W	S
Satine Lens	Satine Lens with White Trim	Satine Lens with Silver Trim
		

Output

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory.
- 90 CRI = R9≥50
- Not all products qualify for DLC listing. For a complete listing of the EV3D products that qualify for DLC, please go to the DLC website.

Custom Output - Lumens OR Wattage

CL_____	Specify CRI, CCT and desired lumens (i.e. CL8351200)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW_____	Specify CRI, CCT and desired wattage (i.e. CW94015)	Specify watts between standard offering listed below

80 CRI

	Color	Output	Watts	Shielding		W		S	
				A		White Trim		Silver Trim	
				Satine Lens					
				Lumens	LPW	Lumens	LPW	Lumens	LPW
830LO	3000K	Low	19.6	2132	108.8	1923	98.1	1814	92.6
830MO	3000K	Middle	30.8	3322	107.9	2996	97.3	2827	91.8
830HO	3000K	High	42.1	4287	101.8	3867	91.9	3648	86.7
835LO	3500K	Low	19.6	2191	111.8	1976	100.8	1865	95.1
835MO	3500K	Middle	30.8	3414	110.8	3079	100.0	2905	94.3
835HO	3500K	High	42.1	4406	104.7	3974	94.4	3750	89.1
840LO	4000K	Low	19.6	2286	116.6	2062	105.2	1945	99.3
840MO	4000K	Middle	30.8	3566	115.8	3217	104.4	3035	98.5
840HO	4000K	High	42.1	4627	109.9	4174	99.1	3938	93.5

90 CRI

927LO	2700K	Low	19.6	1777	90.7	1603	81.8	1512	77.2
927MO	2700K	Middle	30.8	2769	89.9	2497	81.1	2356	76.5
927HO	2700K	High	42.1	3573	84.9	3223	76.6	3041	72.2
930LO	3000K	Low	19.6	1964	100.2	1772	90.4	1671	85.3
930MO	3000K	Middle	30.8	3060	99.4	2760	89.6	2604	84.5
930HO	3000K	High	42.1	3949	93.8	3562	84.6	3361	79.8
935LO	3500K	Low	19.6	1970	100.5	1777	90.7	1676	85.5
935MO	3500K	Middle	30.8	3070	99.7	2769	89.9	2613	84.8
935HO	3500K	High	42.1	3961	94.1	3573	84.9	3371	80.1
940LO	4000K	Low	19.6	2040	104.1	1840	93.9	1736	88.6
940MO	4000K	Middle	30.8	3181	103.3	2869	93.2	2707	87.9
940HO	4000K	High	42.1	4128	98.1	3723	88.4	3513	83.4












Direct Source: MOD Options

- Specify **MOD** in the part number for any of the below options
- All RGB_Source Options will require specific driver and control
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD		Required Driver	Required Control
	Color Changing RGB LED	EC1/EC4	DMX
	Color Changing RGB-W LED	EC1/EC4	DMX
	2 Channel Tunable White		
	Dynamic BIOS		

Mounting

- LUCEN is offered with a universal flange for all grid types. See below for fixture placement in relation to the tile for each grid type
- Grid retention clips integral to housing and require mechanical attachment
- Tie off fixture to structure with retention wires
- Refer to installation instructions during installation at the jobsite
- Approved for dry/damp location when PAF is specified
- Maximum fixture weight is 15lbs - Surface Mount Box adds 10 lbs

G1	G9	GS	FL	S
1" Grid Mount <i>Works with 15/16" grid ceiling types. See profile for fixture position in relation to ceiling grid and tile.</i>	9/16" Grid Mount <i>Works with 9/16" grid ceiling type. For tegular tile installations, fixture position will not be flush to the bottom of the tile. See tegular tile profile image below.</i>	Screw Slot Mounting <i>Works with screw slot and bolt slot grid ceiling types.</i>	Flange Kit <i>A separate flange kit is supplied for installations into inaccessible or drywall applications. Flange kit ships from factory uninstalled separately from fixture.</i>	Surface Mount <i>Utilize for hard lid ceiling applications. The 20 gauge steel frame easily secures to ceiling. Surface Mount Box adds 10 lbs</i>
 <p>Standard Tile</p>  <p>Tegular Tile</p>	 <p>Standard Tile</p>  <p>Tegular Tile</p>	 <p>Tegular Tile</p>	 	 <p>4-5/8" (117.6mm)</p> 

Voltage

- Some LUCEN configurations will not accommodate all voltage options; consult with factory

U	Universal
1	120 volt
2	277 volt
3	347 volt



Driver

- Standard Driver Option = FSD
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more Driver options, see Pinnacle Resource Guide
- Some LUCEN configurations will not accommodate all driver options; consult with factory

0-10V Drivers

FSD	Factory Select Driver 1%, 0-10v
PL2	Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v, requires 347v
OL2	Osram Optotronic, 1%, 0-10v
OL4	Osram Optotronic 347v, 1% 0-10v (requires 347v)
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0-10v, 0.1% Logarithmic
ES2	eldoLED SOLOdrive 0-10v, 0% Linear
OL5	Osram Optotronic 1%, 0-10v, AUX
PL5	Advance Xitanium 1%, 0-10v, AUX

DALI Drivers

OD1	Osram Optotronic 1%, DEXAL
EE3	eldoLED ECOdrive .1%, DALI (logarithmic)
ES3	eldoLED SOLOdrive .1%, DALI (logarithmic)

Lutron Drivers

LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
------------	---

Alternate Drivers

PS1	Signify Advance Xitanium Step Dimming 50%/100%
PR1	Philips Advance Xitanium SR, requires EASYS, VDO or VRF
EH1	ELV 120v only, 0-10v universal
OD1	Osram Optotronic 1%, DEXAL

Driver: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Power Over Ethernet
------------	---------------------

Circuiting

- Select fixture circuiting from options below
- Some LUCEN configurations will not accommodate all circuiting options; consult with factory

1	Single Circuit
E	Emergency Circuit only (uses nIO EZ PH ER with NLIGHT)
N	Night Light Circuit only

Battery & Emergency

- Select battery or emergency options if required
- Battery duration is 90 minutes
- Test button is integral to fixture
- For more Battery options, see Pinnacle Resource Guide

0	No Battery
FSB	Factory Select Battery (10w option)
FSBST	Factory Select Battery (Self Testing)
1P	Bodine 10w Integral, CEC Listed
1IC	Iota 10w Integral, CEC Listed
1G	Bodine GTD
FSG	Factory Select Automatic Load Control Relay (ALCR), UNV
GI	Emergency Transfer Switch (ETS) DR Emergency Control Device, UNV
GB	Bodine GTD, Generator Transfer Device, 120v or 277v

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 10 (watts) x 92.3 (LPW) = 923 battery lumen output

Battery & Emergency Ordering Examples

- Single circuit, 10w integral battery Ordering Code: 1-1P
- Emergency circuit only, 10w integral battery Ordering Code: E-1P

Consult Factory for projects that are larger than 200 units.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

LU22_LED_SPEC_JAN2023



Finish

- Powder-coat white painted finish on exposed trim

W White

Finish: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Wood Grain
	Acoustic
	Metallic Silver
	Textured Black
	Bronze
	Graphite
	Custom Color

Fixture Options

- Additional options to enhance the fixture and finish of the product

QS	10 Day Quick Ship
TW	Through-Wiring
CP	Chicago Plenum
AM	Antimicrobial Paint
FW6	Flex Whip 6'
GLR	Internal Fast Blow Fuse
GMF	Internal Slow Blow Fuse
PAF	Paint after fabrication

Fixture Options: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Remote Driver
	End Power Feed

Quick Ship

Shielding	Output	Mounting	Voltage	Driver	Circuiting	Battery	Finish	Options
10-Day								
A Satine Lens W White Rails S Silver Rails	80 CRI, All color temperatures, all lumen packages <i>See pg 4</i>	G1 1" Grid G9 9/16" Grid GS Grid Screw Slot	U Universal 1 120v 2 277v	FSD Factory Select Driver (1%, 0-10v) PL2 Advance Xitanium 0-10v, 1% OL2 Osram 0-10v, 1%	1 Single E Emergency N Night Light	1P Bodine 10w 1IC Integral Iota 10w Integral	W White	CP Chicago Plenum FW6 Flex Whip 6' 18-gauge GLR Internal Fast-Blow Fuse



Controls

- Pinnacle Lighting offers easy to specify network control solutions that connect to an intelligent centralized system to maximize lighting energy efficiencies or integral sensors for individual fixture control
- Pinnacle Lighting fixtures ship technology ready; commissioning by others
- Controls can only be used with Single Circuit (1) or Emergency Circuit (E)
- Contact factory for any non-standard configurations for layout, placement, or EM options
- Controls only compatible with Satine Lens.
- Must specify required driver in Driver Section

	Solution	Components	Network/Sensor	Connection	Required Drivers	Limitations
DLMFC	Legrand Wattstopper DLM	LMFC-011	Digital Lighting Management (DLM)	Wired, two RJ45 ports	OL2, OL4	Not available with Battery
DLMFS	Legrand Wattstopper LLLC	LMFS-601-W / LMFI-111	Wireless DLM Fixture Sensor	Wireless	OD1, PR1 or 0-10v	0-10v requires interface
EASYS	Philips EasySense	SNS-210	Daylight/PIR Occupancy	Wireless to switches	PR1	Not available with 347 volt
SNSLM	Encelium Sensilum	EN-CLM-PIR-DD-ZB	Encelium, Daylight/PIR Occupancy	Wireless	OD1, OL5	Not available with 347 volt
WLVX	Eaton WaveLinx	SWPD1, MSP3IVMVDC1	WaveLinx WCL, Daylight	Wireless	Any 0-10v	Not available with 347 volt
VDO	Lutron Vive Sensor	DFCSJ-OEM-OCC	Vive, Daylight/PIR Occupancy	Wireless	OD1, PR1	Not available with 347 volt
VRF	Lutron Vive Connected	DFCSJ-OEM-RF	Vive	Wireless	OD1, PR1	Not available with 347 volt
ENLI	Enlighted IOT	SU-5E-IOT, CU-4E	Enlighted, Daylight/PIR Occupancy	Wireless	Any 0-10v	Not available with 347 volt
ENLC	Enlighted Connected Lighting	SU-5E-CL, CU-4E	Enlighted, Daylight/PIR Occupancy	Wireless	Any 0-10v	Not available with 347 volt
ENL2I	Enlighted 2-Wire IOT	KIT-SU-5E-D-IOT	Enlighted, Daylight/PIR Occupancy	Wireless	OD1 OR PR1	Not available with 347 volt
ENL2C	Enlighted 2-Wire Connected Lighting	KIT-SU-5E-D-CL	Enlighted, Daylight/PIR Occupancy	Wireless	OD1 OR PR1	Not available with 347 volt

Controls: MOD Options

- Specify **MOD** in the part number for any of the below options
- Control** Options may require specific driver. Refer to the chart below
- Consult factory for **MOD** specification details, pricing, and lead-time information

		Required Driver
MOD	Encelium Sensilum	OD1, OL5
	Acuity nLight Air Wireless Connected	EE6, ES6

Approvals & Certifications

Construction: Formed 20 gauge cold rolled steel housing. Highly reflective die-formed white painted reflector. Wiring access available on top of housing. Captive and hinged center lens swings open for room-side maintenance of lens, driver and LED boards.

Shielding: Co-extruded acrylic lens with ribbed side channels evenly illuminates the side reflector giving the appearance of a fully luminous aperture. Available with standard satine lens or optional clear lens with linear slot or round perf insert.

Mounting: Designed to install into acoustical grid and inaccessible ceilings. Specify G1, G9 or GS for acoustical grid ceiling. Specify FL for inaccessible ceilings. Grid retention clips integral to housing and require mechanical attachment. Tie off fixture to structure with retention wires. Maximum fixture weight is 28 lbs

LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 107,300 hours and L90 = 32,000 hours. MacAdam 3-Step Ellipses. Not all products are lighting facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

CRI, CCT & Output: Four lumen packages available. Low (LO), Medium (MO), High (HO) and Very High (VHO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on Color Temperature & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 90 CRI = R9≥50.

Voltage: Universal (U), 120 volt (1) and 277 volt (2). Some LUCEN configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Advance Xitanium 0-10V, 1% = PL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 91°F/33°C.

Circuiting: Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). Some LUCEN configurations will not accommodate all circuiting options, consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is integral to fixture.

Finish: Powder-coat white painted finish on exposed trim.

Controls: DLM utilizes wired network connections for digital control through switching and dimming. nLight Air rES7 sensor provides wireless control, daylight harvesting and occupancy detection with PIR or PDT using eldoLED LED drivers. nLight Air rIO module provides wireless control using eldoLED LED drivers. EasySense sensor provides daylight harvesting and PIR occupancy detection using the SR LED driver; the Philips app provides advanced configurations. ENCELUM SensiLUM sensor provides wireless control, daylight harvesting and PIR occupancy; driver data is available when using the DEXAL driver. ENCELUM SensiLUM sensor provides wireless control, daylight harvesting and PIR occupancy; driver data is available when using the DEXAL driver. WaveLinx Connected Lighting sensor provides wireless control and daylight harvesting using 0-10V LED drivers. Lutron Vive sensor provides wireless control, daylight harvesting and PIR occupancy detection using DEXAL or SR LED drivers. Lutron Vive module provides wireless control using DEXAL or SR LED drivers.

Labels: UL and cUL Listed. LO, MO, HO and VHO lumen packages are IC Rated, approved for dry/damp location unless otherwise noted.

Fixture Weight: 15 lbs maximum - Surface Mount Box adds 10 lbs.

Buy American Act Compliant

Warranty: LUCEN LED offered with a 5-year limited warranty. Covers LED, driver and fixture.

For all available IES files, please visit our website at pinnacle-ltg.com. Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP accredited testing laboratory. Testing conducted at 25°C ambient conditions

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

LU22_LED_SPEC_JAN2023