


**QIVI™ Q3S-22DI**  
2' x 2' Direct/Indirect Architectural Shape




**Key Features**

- 6063-T6 Extruded aluminum housing
- Highly reflective = white painted reflector
- Room side maintenance for LED system
- 5-year limited warranty covers LED, driver and fixture
- UL and cUL listed
- Approved for dry/damp location unless otherwise noted
- Maximum weight is 35.8 lbs.
- Buy American Act compliant



Example Part #: Q3S-22DI-A-HE-830HO-830-AC448G1-U-OL2-1-0-W

**Q3S-22DI**



DIRECT SHIELDING		INDIRECT SHIELDING		DIRECT CRI, CCT & OUTPUT		INDIRECT CRI, CCT & OUTPUT	
<b>A</b> - Flat Satine Lens <b>HE</b> - High Efficiency Lens <b>HED</b> - Descent Lens <i>Shielding pg. 2</i>		<b>HE</b> - High Output <b>HEA</b> - Ascent <i>Shielding pg. 2</i>		<b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K <b>40</b> - 4000K <b>CL</b> - Custom Lumens <b>CW</b> - Custom Watts <i>Lumen Output pg. 2</i> Example: 830HO is <b>8</b> = 80 CRI; <b>30</b> = 3000K; <b>HO</b> = High Output; Blank = Standard Output		<b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K <b>40</b> - 4000K <b>CL</b> - Custom Lumens <b>CW</b> - Custom Watts <i>Lumen Output pg. 2 &amp; 3</i>	
MOUNTING <sup>1</sup>		VOLTAGE		DRIVER		CIRCUITING	
<b>AS4</b> - 4 AC to Grid, JB, or ST <b>AH4</b> - 4 AC w/Hub to Grid, JB, or ST <i>Mounting pg. 3</i>		<b>U</b> - Universal (120 thru 277V) <b>1</b> - 120V <b>2</b> - 277V <b>3</b> - 347V <i>Voltage pg. 3</i>		<b>FSD</b> - Factory Select Driver (1%, 0-10v) <b>PL2</b> - Advance Xitanium (1%, 0-10v) <b>OL4</b> - Osram 347V (1%, 0-10v) <b>EE1</b> - eldoLED ECOdrive (1%, 0-10v) <b>ES1</b> - eldoLED SOLOdrive (0%, 0-10v) <b>LH1</b> - Lutron Hi-lume (1%, EcoSystem) <b>PS1</b> - Advance Xitanium (50%/100%) <b>OL2</b> - Osram (1%, 0-10v) <i>Driver pg. 4</i>		<b>1</b> - Single Circuit <b>2</b> - Dual Circuit <b>E</b> - Emergency (entire fixture) <b>N</b> - Night Light (entire fixture) <i>Circuiting pg. 4</i>	
BATTERY & EMERGENCY		FINISH		FIXTURE OPTIONS		CONTROLS	
<b>0</b> - None <b>FSG</b> - Factory Select ALCR <b>GI</b> - Iota ETS DR <b>GB</b> - Bodine GTD <b>PLL</b> - Bodine 10W <b>ILL</b> - Iota 10W Integral (CEC Listed) <b>IG</b> - Bodine GTD <i>Battery and Emergency pg. 4</i>		<b>W</b> - White <b>S</b> - Metallic Silver <b>BL</b> - Textured Black <b>BR</b> - Bronze <b>GR</b> - Graphite <b>CC</b> - Custom Color <i>Finish pg. 4</i>		<b>AM</b> - Antimicrobial Paint <b>GMF</b> - Slow Blow Fuse <b>CC-C</b> - Custom Color Canopy <i>Fixture Options pg. 5</i>		Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.	


<sup>1</sup>Example: AS448JB. AS4 = 4 Aircraft Cables, 48 = 48" long cables, JB = connects to junction box. Standard AC cable lengths are 48" and 120", field adjustable.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Direct Shielding

Indirect Shielding



Output

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory.
- 80 CRI = R9≥19 and 90 CRI = R9≥61

Custom Output - Lumens OR Wattage

<b>CL</b> _____	Specify CRI, CCT and desired lumens (i.e. CL8351200)	Specify lumens between standard offering listed below. Lumens are specified per color temp
<b>CW</b> _____	Specify CRI, CCT and desired wattage (i.e. CW94015)	Specify watts between standard offering listed below

80 CRI

	Color	Lumens	Shielding		HE		HED	
			A		High Efficiency	Descent		
			Satine		LPW	Watts	LPW	Watts
<b>830</b>	3000K	4000	87.7	45.6	100.0	40.0	80.6	49.6
<b>830HO</b>	3000K	6000	85.2	70.4	97.4	61.6	79.8	75.2
<b>830VHO</b>	3000K	8000	84.7	94.4	97.1	82.4	76.3	104.8
<b>835</b>	3500K	4000	90.9	44.0	102.0	39.2	82.0	48.8
<b>835HO</b>	3500K	6000	88.2	68.0	100.0	60.0	78.9	76.0
<b>835VHO</b>	3500K	8000	87.0	92.0	99.0	80.8	77.5	103.2
<b>840</b>	4000K	4000	92.6	43.2	104.2	38.4	82.0	48.8
<b>840HO</b>	4000K	6000	89.3	67.2	101.4	59.2	80.6	74.4
<b>840VHO</b>	4000K	8000	87.7	91.2	100.0	80.0	78.1	102.4

90 CRI

<b>927</b>	2700K	4000	74.6	53.6	82.0	48.8	67.6	59.2
<b>927HO</b>	2700K	6000	73.5	81.6	80.6	74.4	66.4	90.4
<b>930</b>	3000K	4000	75.8	52.8	84.7	47.2	69.4	57.6
<b>930HO</b>	3000K	6000	75.8	79.2	83.3	72.0	68.2	88.0
<b>935</b>	3500K	4000	78.1	51.2	87.7	45.6	70.4	56.8
<b>935HO</b>	3500K	6000	77.3	77.6	85.2	70.4	70.1	85.6
<b>940</b>	4000K	4000	76.9	52.0	86.2	46.4	70.4	56.8
<b>940HO</b>	4000K	6000	77.3	77.6	85.2	70.4	69.4	86.4

Indirect 80 CRI

	Color	Lumens	HE		HEA	
			High Efficiency	Ascent	LPW	Watts
<b>830</b>	3000K	4000	122.0	32.8	119.0	33.6
<b>830HO</b>	3000K	6000	121.0	49.6	117.2	51.2
<b>830VHO</b>	3000K	8000	119.0	67.2	114.9	69.6
<b>835</b>	3500K	4000	125.0	32.0	119.0	33.6
<b>835HO</b>	3500K	6000	123.0	48.8	121.0	49.6
<b>835VHO</b>	3500K	8000	122.0	65.6	117.6	68.0
<b>840</b>	4000K	4000	125.0	32.0	128.2	31.2
<b>840HO</b>	4000K	6000	125.0	48.0	127.1	47.2
<b>840VHO</b>	4000K	8000	123.5	64.8	126.6	63.2



Output - Continued

Indirect 90 CRI

			HE		HEA	
			High Efficiency	Ascent	LPW	Watts
<b>927</b>	2700K	6000	102.0	39.2	100.0	40.0
<b>927HO</b>	2700K	9000	101.4	59.2	98.7	60.8
<b>927VHO</b>	2700K	12000	102.0	78.4	98.0	81.6
<b>930</b>	3000K	6000	106.4	37.6	104.2	38.4
<b>930HO</b>	3000K	9000	105.6	56.8	101.4	59.2
<b>930VHO</b>	3000K	12000	105.3	76.0	102.0	78.4
<b>935</b>	3500K	6000	108.7	36.8	106.4	37.6
<b>935HO</b>	3500K	9000	107.1	56.0	104.2	57.6
<b>935VHO</b>	3500K	12000	104.2	76.8	104.2	76.8
<b>940</b>	4000K	6000	108.7	36.8	104.2	38.4
<b>940HO</b>	4000K	9000	105.6	56.8	104.2	57.6
<b>940VHO</b>	4000K	12000	106.4	75.2	103.1	77.6

Mounting

- Aircraft cables mount directly to a standard junctionbox or structure
- Canopies, hubs, and pendants match fixture finish, power cords are white, grey, or black depending on fixture finish. See Finish section for additional details
- AH4 canopies can be installed below the ceiling plane or semi-recessed into the ceiling for a flush mount installation, no specification required (see below)



- Must specify cable length, either 48" or 120" standard, field adjustable
- Designed to install into acoustical grid and inaccessible ceilings
- Tie off fixture to structure with retention wires
- Maximum fixture weight is 35.8 lbs

**AS4 JB**  
4 AC cables to fixture to J-Box

**AH4 JB**  
4 AC cables with hub to fixture to J-Box


**AS4 ST**  
4 AC cables to fixture to Structure

**AH4 ST**  
4 AC cables with hub to fixture to Structure



AH4 Canopy Options

- The canopy can be installed either below the ceiling plane or semi-recessed into the ceiling for a flush mount installation
- Standard kit can be installed either way
- Flush canopy installation is not available for fixtures installed below a grid rail



Voltage

- Some QIVI configurations will not accommodate all voltage options; consult with factory

<b>U</b>	Universal
<b>1</b>	120 volt
<b>2</b>	277 volt
<b>3</b>	347 volt



## Driver

- Standard Driver Option = PL2
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- Some QIVI configurations will not accommodate all driver options; consult with factory

### 0-10V Drivers

<b>FSD</b>	Factory Select Driver 1%, 0-10v
<b>PL2</b>	Signify Advance Xitanium 1%, 0-10v
<b>PL4</b>	Advance Xitanium 347v 1%, 0-10v, requires 347v
<b>OL2</b>	Osram Optotronic, 1%, 0-10v
<b>OL4</b>	Osram Optotronic 347v, 1% 0-10v, requires 347v option
<b>EE1</b>	eldoLED ECOdrive 1%, 0-10v Logarithmic
<b>EE2</b>	eldoLED ECOdrive 1%, 0-10v Linear
<b>ES1</b>	eldoLED SOLOdrive 0-10v, 0% Logarithmic
<b>ES2</b>	eldoLED SOLOdrive 0-10v, 0% Linear

### DALI Drivers

<b>EE3</b>	eldoLED SOLOdrive .1%, DALI (logarithmic)
<b>EE4</b>	eldoLED SOLOdrive .1%, DALI (linear)
<b>OD1</b>	Osram Optotronic 1%, DEXAL
<b>OD2</b>	Osram Optotronic 1%, DALI 2 Channel

### Lutron Drivers

<b>LH1</b>	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
<b>LH4</b>	Lutron Hi-Lume 1%, 2-wire, Lutron-LTEA2W, 120v only

### Alternate Drivers

<b>PS1</b>	Signify Advance Xitanium Step Dimming 50%/100%
<b>EH1</b>	ELV 120v only, 0-10v universal

## Circuiting

- Select fixture circuiting from options below
- Some QIVI configurations will not accommodate all circuiting options; consult with factory

<b>1</b>	Single Circuit
<b>2</b>	Dual Circuit
<b>E</b>	Emergency Circuit only
<b>N</b>	Night Light Circuit only

## Battery

- Select battery section type if required, indicate total QTY. *Example 2P*
- 90 minute battery runtime; test button is remote to fixture and requires an additional drop
- For more battery options available, see Pinnacle Resource Guide

<b>0</b>	No battery
<b>_FSG</b>	Factory Select ALCR, Automatic Load Control Relay
<b>_GI</b>	Iota ETS DR, Emergency Lighting Control Device
<b>_GB</b>	Bodine GTD, Emergency Lighting Control Device
<b>_PLL</b>	Bodine 10w Integral Lithium ( <i>self testing</i> )
<b>_ILL</b>	Iota 10w Integral Lithium ( <i>self testing</i> )
<b>1G</b>	Bodine GTD, Generator Transfer Device

### For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 92.3 (LPW) x 10 (watts) = 923 battery lumen output

### Battery OR Emergency Ordering Examples

- Single circuit, 10w Integral Battery      Ordering Code: 1-1P
- Emergency only, 10w Integral Battery      Ordering Code: E-1P

## Finish

- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

<b>W</b>	White ( <i>white cord/white canopy</i> )
<b>S</b>	Metallic Silver ( <i>grey cord/silver canopy</i> )
<b>BL</b>	Textured Black ( <i>black cord/black canopy</i> )
<b>BR</b>	Bronze ( <i>white cord/bronze canopy</i> )
<b>GR</b>	Graphite ( <i>white cord/graphite canopy</i> )
<b>CC</b>	Custom Color ( <i>white cord/color match canopy</i> )

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

Q3S-22DI\_LED\_SPEC\_OCT2021



## Fixture Options

- Additional options to enhance the fixture and finish of the product

<b>AM</b>	Antimicrobial Paint
<b>GMF</b>	Internal Slow Blow Fuse
<b>CC-C</b>	Custom Color Canopy


## Controls

- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

## Photometrics

### High Efficiency Lens

Test #	PRELIMINARY
Catalog #	Q3S-22DI-840-840
Lumens	8000 lm
Watts	70.4 W
Efficacy	114 LPW



## Approvals & Certifications

**Construction:** 6063-T6 Extruded aluminum housing. Highly reflective steel white painted reflector.

**Shielding:** Diffuse snap-in acrylic lens, removable for maintenance.

**Mounting:** Designed to install into acoustical grid and inaccessible ceilings. Tie off fixture to structure with retention wires. Maximum fixture weight is 35.8 lbs

**LED:** 25°C test environment. Lumen output/wattage has a margin of +/- 5%. All luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 136,200 hours and L90 = 41,100 hours. MacAdam 3-Step Ellipses. Not all products are Lighting Facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

**CRI, CCT & Output:** Two lumen packages available. Standard and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 80 CRI = R9≥19 and 90 CRI = R9≥61.

**Voltage:** Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL4 in Driver section when 347 volt (3) is selected. Some QIVI configurations will not accommodate all voltage options; consult with factory.

**Driver:** Standard Driver Option is Advance Xitanium 0-10V, 1% = PL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 95°F/35°C. Some QIVI configurations will not accommodate all driver options.

**Circuiting:** Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some QIVI configurations will not accommodate all circuiting options, consult with factory.

**Finish:** Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes. Canopies painted white unless specified differently in the options section of the part number. Contact factory for additional custom color and finish options.

**Controls:** Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

**Labels:** UL and cUL Listed. STD, HO and VHO lumen packages are approved for dry/damp location unless otherwise noted.

**Fixture Weight:** Maximum fixture weight is 35.8 lbs.

**Buy American Act Compliant**

**Warranty:** QIVI offered with a 5-year limited warranty. Covers LED, driver and fixture.