


CONVERJ CJ14

1x4 Architectural Recessed




Key Features

- Formed 22 gauge cold rolled steel housing.
- Highly reflective die-formed white painted reflector
- Wiring access available on top of housing
- LED offered with a 5-year limited warranty. Covers LED, driver and fixture
- UL and cUL Listed, LO, MO and HO lumen packages are IC Rated
- For damp location, must specify Paint After Fabrication (PAF) in the Options section of the luminaire specification
- Maximum fixture weight is 15 lbs - Surface Mount Box adds 10 lbs
- Room-Side Maintenance for LED system



Example Part #: CJ14-A-835HO-G1-U-FSD-1-0-W

CJ14



SHIELDING	CRI, CCT & OUTPUT ^{1, 2}	MOUNTING	VOLTAGE ³
A - Satine Lens R - Round Perf <i>Shielding pg. 2</i>	27 _ - 2700K 30 _ - 3000K 35 _ - 3500K 40 _ - 4000K TW _ - 2CH Tunable White (2700-6500K, 90CRI) CL _ _ _ - Custom Lumens CW _ _ _ - Custom Watts <i>Lumen Output pg. 2</i>	G1 - 15/16" Grid G9 - 9/16" Grid GS - Screw Slot Grid FL - Flanged S - Surface Mount <i>Mounting pg. 3</i>	U - Universal (120 thru 277V) 1 - 120V 2 - 277V 3 - 347V <i>Voltage pg. 3</i>

DRIVER	CIRCUITING ⁴	BATTERY & EMERGENCY	FINISH
FSD - Factory Select Driver (1%, 0-10v) PL2 - Advance Xitanium (1%, 0-10v) OL2 - eldoLED Optotronic (1%, 0-10v) OL4 - eldoLED Optotronic 347v (1%, 0-10v) EE1 - eldoLED ECoDrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0.1%, 0-10v) LH1 - Lutron Hi-lume (1%, EcoSystem) PR1 - Advance Xitanium SR <i>Driver pg. 3</i>	1 - Single Circuit E - Emergency (<i>entire fixture</i>) N - Night Light (<i>entire fixture</i>) <i>Circuiting pg. 4</i>	0 - None FSB - Factory Select Battery FSG - Factory Select ALCR GI - Iota ETS DR GB - Bodine GTD 1ILL - Iota 10W 1PLL - Bodine 10W <i>Battery and Emergency pg. 4</i>	W - White <i>Finish pg. 4</i>

FIXTURE OPTIONS	CONTROLS
TW - Through-wiring CP - Chicago Plenum AM - Antimicrobial Paint DSP - Customer Supplied Battery/Driver/ Sensor FW6 - 6' Flex Whip GLR - Fast Blow Fusing GMF - Slow Blow Fusing BA - Buy American Act Compliant <i>Fixture Options pg. 5</i>	<i>Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.</i>


¹When specifying SOURCE the first _ is for specifying either **8** - 80CRI, **9** - 90CRI. The ending _ _ are for specifying output, example 835HO - 80CRI, 3500K High Output. See output charts for more information. ²When specifying Tunable White, use **TW** and then specify output, example TWH0 - Tunable White 90CRI, High Output 2700-6500K. See output charts for more information. Tunable White option requires driver option **FSD** which provides separate 0-10v control leads for Intensity and CCT. ³Tunable White (**TW**) option only available with Universal (**U**), 120V (**1**) or 277V (**2**) options. ⁴Consult factory for Emergency (**E**) or Night Light (**N**) options with Tunable White option.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Shielding

- Unique twin-arched wings and articulated center spine
- Utilizes a proprietary layered lens creating a fully luminous housing with optimal glare control
- Highly reflective white reflectors maintain uniform lens brightness
- Wiring access available on both side and top of housing



Output

- Specify either 80 or 90 CRI for White light LED
- Longer lead-time may apply for 90 CRI or Tunable White option. Consult factory
- Tunable White option requires driver option FSD which provides separate 0-10v control leads for Intensity and CCT.
- Tunable White lumen packages shown at 4000K CCT setpoint
- 90 CRI = R9≥50

Custom Output - Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL8351200)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW _____	Specify CRI, CCT and desired wattage (i.e. CW94015)	Specify watts between standard offering listed below
CLTW _____	Specify desired lumens for Tunable White (i.e. CLTW3200)	Specify lumens between Tunable White offering listed below. Lumens are specified at 4000K CCT setpoint.

80 CRI

	Color	Output	Watts	Shielding			
				A Satine Lens		R Round Perf	
				Lumens	LPW	Lumens	LPW
830LO	3000K	Low	15.7	1995	127	1571	100
830MO		Middle	23.9	2994	125	2359	99
830HO		High	33.7	4144	123	3264	97
835LO	3500K	Low	15.7	2003	128	1578	101
835MO		Middle	23.9	3007	126	2369	99
835HO		High	33.7	4162	123	3278	97
840LO	4000K	Low	15.7	2057	131	1620	103
840MO		Middle	23.9	3088	129	2432	102
840HO		High	33.7	4273	127	3366	100

90 CRI

927LO	2700K	Low	15.7	1654	105	1303	83
927MO		Middle	23.9	2483	104	1956	82
927HO		High	33.7	3437	102	2707	80
930LO	3000K	Low	15.7	1695	108	1335	85
930MO		Middle	23.9	2544	106	2004	84
930HO		High	33.7	3520	104	2773	82
935LO	3500K	Low	15.7	1769	113	1393	89
935MO		Middle	23.9	2654	111	2091	87
935HO		High	33.7	3674	109	2894	86
940LO	4000K	Low	15.7	1816	116	1430	91
940MO		Middle	23.9	2725	114	2146	90
940HO		High	33.7	3771	112	2971	88









2 CH Tunable White (2700-6500K, 90CRI)

TWLO	2700 - 6500K	Low	20.9	2000	95.9	1599	76.7
TWMO		Middle	31.5	3000	95.3	2356	74.8
TWHO		High	45.1	4100	90.9	3274	72.6



Mounting

- CONVERJ is offered with a universal flange for all grid types. See below for fixture placement in relation to the tile for each grid type
- Grid retention clips integral to housing and require mechanical attachment
- Tie off fixture to structure with retention wires
- Maximum fixture weight is 15 lbs - Surface Mount Box adds 10 lbs
- Refer to installation instructions during installation at the job site

G1	G9	GS	FL	S
1" Grid Mount <i>Works with 15/16" grid ceiling types. See profile for fixture position in relation to ceiling grid and tile.</i>	9/16" Grid Mount <i>Works with 9/16" grid ceiling type. For tegular tile installations, fixture position will not be flush to the bottom of the tile. See tegular tile profile image below.</i>	Screw Slot Mounting <i>Works with screw slot, bolt slot and 9/16" grid ceiling types. For 9/16" installations with tegular tile, fixture position will be flush to the bottom of the tile. Consult factory for detailed installation instructions.</i>	Flange Kit <i>A separate flange kit is supplied for installations into inaccessible or drywall applications. Flange kit ships from factory uninstalled separately from fixture. Consult factory for detailed installation instructions.</i>	Surface Mount <i>Utilize for hard lid ceiling applications. The 20 gauge steel frame easily secures to ceiling. Surface Mount Box adds 10 lbs.</i>
 <p>Standard Tile</p>  <p>Tegular Tile</p>	 <p>Standard Tile</p>  <p>Tegular Tile</p>			 <p>4-5/8" (117.6mm)</p> 

Voltage

- Some CONVERJ configurations will not accommodate all voltage options; consult with factory
- 347 volt not available with Tunable White (TW) option

U	Universal
1	120 volt
2	277 volt
3	347 volt



Driver

- Standard Driver Option = FSD 1%, 0-10v
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more Driver options, see Pinnacle Resource Guide
- Some CONVERJ configurations will not accommodate all driver options; consult with factory

0-10V Drivers

FSD	Factory Select Driver 1%, 0-10v
PL2	Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v <i>(requires 347v)</i>
OL2	eldoLED Optotronic, 1%, 0-10v
OL4	eldoLED Optotronic 347v, 1% 0-10v <i>(requires 347v)</i>
EE1	eldoLED ECOdrive 1%, 0-10v, Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v, Linear
ES1	eldoLED SOLOdrive 0.1%, 0-10v, Logarithmic
ES2	eldoLED SOLOdrive 0.1%, 0-10v, Linear
OL5	eldoLED Optotronic 1%, 0-10v, AUX, Dim to Off
PL5	Advance Xitanium 1%, 0-10v, AUX, Dim to Off

DALI Drivers

EE3	eldoLED ECOdrive 1%, DALI 2, Logarithmic, DT6
ES3	eldoLED SOLOdrive 0.1%, DALI 2, Logarithmic, DT6
OD1	eldoLED Optotronic 1%, DEXAL, DALI 2, DT6, Self powered link
PR1	Advance Xitanium SR, DALI 2, Self powered link

Lutron Drivers

LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
------------	---

Alternate Drivers

PS1	Advance Xitanium Step Dimming 50%/100%
EH1	ERP 1%, Line Voltage and ELV <i>(requires 120v)</i>

Circuiting

- Select fixture circuiting from options below
- Some CONVERJ configurations will not accommodate all circuiting options; consult with factory
- Consult factory for Emergency (E) or Night Light (N) circuit with Tunable White (TW) option

1	Single Circuit
E	Emergency Circuit only
N	Night Light Circuit only

Battery & Emergency

- Select battery or emergency options if required
- Battery duration is 90 minutes
- For Tunable White (TW) option, battery with illuminate 6500K LED unless otherwise specified.
- Test button is integral to fixture
- For more Battery options, see Pinnacle Resource Guide
- Consult factory for Emergency Control Devices with Tunable White (TW) option

0	No Battery
FSB	Factory Select Battery (10w option)
FSBST	Factory Select Battery (10w, Self Testing)
FSG	Factory Select ALCR Emergency Control Device, UNV
GI	Iota ETS-DR, Emergency Control Device, UNV
GB	Bodine GTD, Emergency Control Device, 120v or 277v
1ILL	Iota 10w Integral Lithium, Self Testing
1PLL	Bodine 10w Integral Lithium, Self Testing

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 10 (watts) x 120 (LPW) = 1200 battery lumen output

Battery & Emergency Ordering Examples

- Single circuit, 10w integral battery Ordering Code: 1-1FSB
- Emergency circuit only, 10w integral battery Ordering Code: E-1ILL

Finish

- Powder-coat white painted finish

W	White
----------	-------



Fixture Options

- Additional options to enhance the fixture and finish of the product

TW	Through-Wiring
CP	Chicago Plenum
AM	Antimicrobial Paint
FW6	Flex Whip 6'
GLR	Internal Fast Blow Fuse
GMF	Internal Slow Blow Fuse
BA	Buy American Act Compliant
DSP	Customer Supplied Battery/Driver/Sensor


Controls

- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

Photometrics

Satine Lens

Test #	KPL2015-94
Catalog #	CJ14-A-840HO
Lumens	4249 lm
Watts	33.9W
Efficacy	125 LPW



Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	1588	1588	1588	1588	1588
5	1583	1584	1578	1577	1578
10	1561	1562	1555	1555	1555
15	1523	1525	1519	1518	1519
20	1472	1473	1468	1467	1466
25	1411	1409	1405	1401	1400
30	1333	1331	1325	1321	1318
35	1246	1243	1233	1229	1227
40	1147	1143	1133	1126	1122
45	1039	1033	1020	1013	1007
50	918	913	895	886	881
55	792	783	766	756	747
60	655	644	626	609	600
65	513	505	483	464	457
70	371	365	343	327	321
75	240	235	219	207	200
80	125	130	120	117	116
85	46	51	53	55	54
90	0	0	0	0	0

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4971	4880	4818
55	4669	4516	4405
65	4106	3870	3658
75	3136	2869	2615
85	1790	2058	2109



Approvals & Certifications

Construction: Pre-painted formed 22 gauge cold rolled steel housing. Highly reflective die-formed reflectors maintain uniform lens brightness. Wiring access on both sides and top of housing. Housing designed to maintain optimal temperature of LED diodes and driver. Captive door frame swings open for room-side maintenance of lens, driver and LED boards.

Shielding: Single piece co-extruded unique twin-arched wings and articulated center spine. Utilizes a proprietary layered lens creating a fully luminous housing with optimal glare control. Available with standard satine lens.

Mounting: Designed to install into acoustical grid and inaccessible ceilings. Specify G1, G9 or GS for acoustical grid ceiling. Specify FL for inaccessible ceilings. Grid retention clips integral to housing and require mechanical attachment. Tie off fixture to structure with retention wires. Maximum fixture weight is 15 lbs - Surface Mount Box adds 10 lbs.

White LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 123,100 hours and L90 = 36,700 hours. MacAdam 3-Step Ellipses. Not all products are lighting facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

Tunable White LED: 2 channel solution with 2700K and 6500K LED, 90CRI only, R9 >50. Lumen packages available shown at 4000K CCT setpoint, lumen output varies based on CCT. Use multipliers for other CCT; 2700K = .91 3000K = .93 3500K = .97 4000K = 1.0 5000K = 1.04 6500K = 1.078.

Color & Lumen Output: Three lumen packages available. Low (LO), Medium (MO), and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 90 CRI = R9≥50.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL4 in Driver section when 347 volt (3) is selected. Some CONVERJ configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Advance Xitanium 0-10V, 1% = PL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 91°F/33°C. For more driver options, see Pinnacle Resource Guide. Some CONVERJ configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). Some CONVERJ configurations will not accommodate all circuiting options, consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is integral to fixture. For more Battery options, see Pinnacle Resource Guide.

Finish: Powder coat white painted finish

Labels: UL and cUL 1598 listed. LO, MO, and HO lumen packages are IC Rated. Approved for dry/damp location unless otherwise noted.

Fixture Weight: 15 lbs maximum - Surface Mount Box adds 10 lbs.

Warranty: CONVERJ LED offered with a 5-year limited warranty. Covers LED, driver and fixture.