


EDGE EX3D

3" Suspended Direct Linear

Key Features

- 6063-T6 Extruded aluminum housing
- Room side maintenance for LED system
- 5-year limited warranty covers LED, driver and fixture
- ETL listed conforming to UL 1598 in US and CSA 250 in Canada
- Approved for dry/damp location unless otherwise noted
- Maximum weight is 20 lbs. for a standard 4' fixture
- Buy American Act compliant
- Run lengths available to an 1/8"
- Product transparency with third-party verified Living Building Challenge (LBC) Declared



Example Part #: EX3D-HE-N-830HO-26'-AC48G1-U-FSD-1-0-W


EX3D -		- N																					
DIRECT SHIELDING		INDIRECT SHIELDING		SOURCE		LENGTH OR PATTERN		MOUNTING		VOLTAGE		DRIVER		CIRCUITING		BATTERY & EMERGENCY		FINISH		FIXTURE OPTIONS		CONTROLS	
--				N				-----				----											
DIRECT SHIELDING				INDIRECT SHIELDING				SOURCE <i>QS</i> ^{1,2}				LENGTH OR PATTERN ³											
A - Satine Lens <i>QS</i> AL - Drop Lens HE - High Efficiency <i>QS</i> BW - Batwing <i>QS</i> WHE - Asymmetric <i>QS</i> HED - Descent <i>Shielding pg. 2</i>				N - None <i>Shielding pg. 2</i>				27 -- - 2700K 30 -- - 3000K 35 -- - 3500K 40 -- - 4000K TW -- - 2CH Tunable White (2700-6500K, 90CRI) CL ----- - Custom Lumens CW ----- - Custom Watts MOD - Mod options available <i>Lumen Output pg. 2</i>				-- - Individual Fixture <i>QS</i> -- - Continuous Row <i>QS</i> S -- - Square <i>QS</i> R_x -- - Rectangle <i>QS</i> L_x -- - L Shape <i>QS</i> U_x -- - U-Shape <i>QS</i> T_x -- - T-Shape X_x_x -- - X-Shape MOD - Mod options available <i>Length and Pattern pg. 3</i>											
-----				-				----				-											
MOUNTING ⁴				VOLTAGE ⁵				DRIVER				CIRCUITING ⁶											
AC_G - (M)AC to Grid <i>QS</i> AC_JB - (M)AC to J Box <i>QS</i> AC_ST - (M)AC to Structure <i>QS</i> AC5_G - 5" Non-Power Canopy AC5_JB - 5" Non-Power Canopy SQ_G - 5" Square Canopy SQ_JB - 5" Square Canopy WA - Wall Mount <i>QS</i> S - Surface Mount <i>QS</i> MOD - Mod options available <i>Mounting pg. 3</i>				U - Universal (120 thru 277V) <i>QS</i> 1 - 120V <i>QS</i> 2 - 277V <i>QS</i> 3 - 347V <i>Voltage pg. 4</i>				FSD - Factory Select Driver (1%, 0-10v) <i>QS</i> PL2 - Advance Xitanium (1%, 0-10v) OL2 - eldoLED Optotronic (1%, 0-10v) OL4 - eldoLED Optotronic 347v (1%, 0-10v) EE1 - eldoLED ECODrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0.1%, 0-10v) LH1 - Lutron Hi-lume (1%, EcoSystem) PS1 - Advance Xitanium (50%/100%) MOD - Mod options available <i>Driver pg. 5</i>				1 - Single Circuit <i>QS</i> M - Multi Circuit E - Emergency (entire fixture) <i>QS</i> N - Night Light (entire fixture) <i>QS</i> <i>Circuiting pg. 5</i>											
---				--				----				---											
BATTERY & EMERGENCY ⁷				FINISH				FIXTURE OPTIONS ⁸				CONTROLS ⁹											
0 - None <i>QS</i> FSB - Factory Select Battery <i>QS</i> FSG - Factory Select ALCR GI - Iota ETS DR GB - Bodine GTD ILL - Iota 10W Integral PLL - Bodine 10W <i>Battery and Emergency pg. 6</i>				W - White <i>QS</i> S - Metallic Silver <i>QS</i> BL - Textured Black <i>QS</i> BR - Bronze GR - Graphite CC - Custom Color <i>Finish pg. 6</i>				QS - Quick Ship <i>QS</i> TC - Indirect Top Cover (ac mounting only) LMRA - Adjustable MR16 (LED) XLED - Fixed Xicato LED DSP - Customer Supplied Battery/Driver/ Sensor MOD - Mod options available <i>Fixture Options pg. 6</i>				DLMFS - Wattstopper LLC (wireless) EASYS - Philips EasySense (wireless) NSLM - Encelium Sensillum (wireless) WVLX - Eaton WaveLinX (wireless) VDO - Lutron Vive Sensor (wireless) VRF - Lutron Vive Connected (wireless) MOD - Mod options available <i>Controls pg. 7</i>											

¹When specifying SOURCE the first _ is for specifying either 8 - 80CRI, 9 - 90CRI. The ending _ _ are for specifying output, example 835HO - 80CRI, 3500K High Output. See output charts for more information. ²When specifying Tunable White, use TW and then specify output, example TWHO - Tunable White 90CRI, High Output 2700-6500K. See output charts for more information. Tunable White option requires driver option FSD which provides separate 0-10v control leads for Intensity and CCT. ³Individual fixtures come in 2', 3', 4', 5', 6', 7' & 8' lengths. Continuous row come in 1/8" increments. For Patterns specify pattern shape and overall dimensions. Example: L6x4: L pattern that is 6'x4'. ⁴Specify AC Cable: Standard single AC = AC or Movable AC = MAC; Specify AC length standard AC is 48"; Specify grid: G1=15/16", G9=9/16" GS=Screw Slot. Example: AC48G1 ⁵Tunable White (TW) option only available with Universal (U), 120V (1) or 277V (2) options. ⁶Consult factory for Emergency (E) or Night Light (N) options with Tunable White (TW) option. ⁷Enter quantity for Battery and Emergency, Example 2P. ⁸When ordering QuickShip, QS must be used in fixture options section of part number to qualify. 1/8" increments not available for QS. LMRA only available with 120v (1) voltage option. ⁹Controls can only be used with Single Circuit (1) or Emergency Circuit (E). See Controls chart on page 5 for driver options and more information.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Direct Shielding



Indirect Shielding

N
None

Source

- Specify either 80 or 90 CRI for White light LED
- Longer lead-time may apply for 90 CRI or Tunable White option. Consult factory
- Tunable White option requires driver option FSD which provides separate 0-10v control leads for Intensity and CCT.
- Tunable White lumen packages shown at 4000K CCT setpoint
- 90 CRI = R9≥50

Custom Output - Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL835500)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW _____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Specify watts between standard offering listed below
CLTW _____	Specify desired lumens for Tunable White (i.e. CLTW3200)	Specify lumens between Tunable White offering listed below. Lumens are specified at 4000K CCT setpoint.

80 CRI

	Color	Lumens per foot	Shielding¹											
			A		AL		HE		BW		WHE		HED	
			Satine LPW	Watts/ft	Drop LPW	Watts/ft	High Efficiency LPW	Watts/ft	Batwing LPW	Watts/ft	Asymmetric LPW	Watts/ft	Descent LPW	Watts/ft
830	3000K	500	108	4.6	118	4.2	123	4.1	120	4.2	124	4.0	106	4.7
830HO		750	110	6.8	117	6.4	128	5.9	119	6.3	123	6.1	108	6.9
830VHO		1000	110	9.1	120	8.3	131	7.6	122	8.2	126	7.9	109	9.2
835	3500K	500	111	4.5	122	4.1	127	3.9	123	4.1	123	4.1	110	4.6
835HO		750	111	6.8	121	6.2	132	5.7	123	6.1	127	5.9	112	6.7
835VHO		1000	114	8.8	124	8.0	133	7.5	126	7.9	131	7.7	113	8.9
840	4000K	500	111	4.5	122	4.1	127	3.9	123	4.1	123	4.1	110	4.6
840HO		750	111	6.8	121	6.2	132	5.7	123	6.1	127	5.9	112	6.7
840VHO		1000	114	8.8	124	8.0	133	7.5	126	7.9	131	7.7	113	8.9

90 CRI

927	2700K	500	89	5.6	98	5.1	104	4.8	99	5.0	102	4.9	88	5.7
927HO		750	90	8.3	99	7.6	106	7.1	99	7.6	102	7.3	89	8.4
927VHO		1000	90	11.1	99	10.1	106	9.4	100	10.0	104	9.7	88	11.4
930	3000K	500	97	5.1	104	4.8	113	4.4	106	4.7	109	4.6	96	5.2
930HO		750	99	7.6	106	7.0	113	6.6	108	6.9	112	6.7	97	7.7
930VHO		1000	98	10.2	107	9.4	116	8.6	108	9.2	112	8.9	97	10.3
935	3500K	500	97	5.2	104	4.8	113	4.4	105	4.7	109	4.6	96	5.2
935HO		750	98	7.6	106	7.1	112	6.7	108	7.0	111	6.7	97	7.7
935VHO		1000	98	10.2	106	9.4	116	8.6	108	9.3	112	9.0	97	10.3
940	4000K	500	97	5.2	104	4.8	113	4.4	105	4.7	109	4.6	96	5.2
940HO		750	98	7.6	106	7.1	112	6.7	108	7.0	111	6.7	97	7.7
940VHO		1000	98	10.2	106	9.4	116	8.6	108	9.3	112	9.0	97	10.3

2 CH Tunable White (2700-6500K, 90CRI)

TW	2700 - 6500K	500	86.5	5.8	N/A	102.7	4.9	95.8	5.2	99.0	5.0	N/A
TWHO		750	82.4	9.1		99.6	7.5	82.4	9.1	95.6	7.8	
TWVHO		1000	N/A			94.5	10.9	N/A		90.6	11.0	



Direct Source: MOD Options

- Specify **MOD** in the part number for any of the below options
- All RGB_ Source Options will require specific driver and control

- Consult factory for **MOD** specification details, pricing, and lead-time information


MOD	Color Changing RGB LED Color Changing RGB-W LED	Required Driver	Required Control
		EC1/EC4	DMX
MOD	Color Changing RGB LED Color Changing RGB-W LED	EC1/EC4	DMX

Length

- Individual units cannot be joined, end plates are factory installed and cannot be removed
- For Continuous Runs, add 3/16" (4.7mm) for each end plate or 3/8" (9.5mm) to the overall length of the row
- For patterns, refer to Pattern section on next page


2	3	4	5	6	7	8	—
Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Cont. Run Specify nominal overall row length to the 1/8" Longer lead-time may apply for lengths to the 1/8". Consult factory.
24-3/8" (619.1mm)	36-3/8" (934.8mm)	48-3/8" (1228.7mm)	60-3/8" (1533.5mm)	72-3/8" (1838.3mm)	84-3/8" (2143.1mm)	96-3/8" (2447.9mm)	
Specify to the 1/8" >>>>							

Pattern



- Specify pattern shape and overall dimensions (includes corner dimensions)
- Refer to dimensions table below for available standard lengths
- All connectors are direct only
- 90 degree horizontal corners are 12"x12" (overall, outside dimension)
- Angles and shapes not shown require Mod Pattern; consult factory
- Only available with "A" or "HE" lens options

S_	R_x	U_x x	L_x	T_x	X_x
Square Provide A dimension Example: S4' Minimum Length- 4'x4'	Rectangle Provide Ax B dimensions Example: R4'x4' Minimum Length- 4'x4'	U-Shape Provide Ax BxC dimensions Example: U3'x4'x3' Minimum Length- 3'x4'x3'	L-Shape Provide Ax B dimensions Example: L3'x3' Minimum Length- 3'x3'	T-Shape Provide Ax B dimensions Example: T3'x5' Minimum Length- 3'x5'	X-Shape Provide Ax B dimensions Example: X5'x5' Minimum Length- 5'x5'




Length or Pattern: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Specify MOD for patterns, lengths or angles not shown above
	45- 180 degree angles
	Single-piece welded housings up to 4' x 4'

Horizontal Details: Every Connection is 12" x 12" in Overall Dimension






Mounting


- Specify cable length in ordering code (AC48G1)
- Standard adjustable cable, specify 48", 120", 240", or 350"
- End plates and power cord attached at factory
- Aircraft cable (AC) mounts on 4' (1219.2mm) and 8' (2438.4mm) centers
- Maximum recommended movable mounting locations are 12" from end of 4' fixture and 18" from end of 8' fixture
- Aircraft Cable supplied with 5" (127mm) power and 2" (50.8mm) non-power canopies

- Canopies and pendants match fixture finish, power cords are white or black depending on fixture finish. See Finish section for additional details.
- Approved for dry/damp location unless otherwise noted
- Refer to installation instructions during installation at the job site
- Maximum fixture weight is 20 lbs for a standard 4' fixture
- Top Cover is optional on AC mounting fixtures, Top Cover is standard on others

AC_G1	Aircraft Cable 1" (15/16") T-Bar
AC_G9	Aircraft Cable 9/16" T-Bar
AC_GS	Aircraft Cable Screw Slot T-Bar
AC_JB	Aircraft Cable Junction Box
AC_ST	Aircraft Cable Structure
AC5_G	Aircraft Cable 5" (127mm) Non-Power Canopy
AC5_JB	Aircraft Cable 5" (127mm) Non-Power Canopy
SQ_G	Aircraft Cable 5" (127mm) Square Canopy
SQ_JB	Aircraft Cable 5" (127mm) Square Canopy
MAC_G1	Movable AC 1" (15/16") T-Bar
MAC_G9	Movable AC 9/16" T-Bar
MAC_GS	Movable AC Screw Slot T-Bar
MAC_JB	Movable AC Junction Box
MAC_ST	Movable AC Structure
MAC5_G	Movable AC 5" (127mm) Non-Power Canopy
MAC5_JB	Movable AC 5" (127mm) Non-Power Canopy
MSQ_G	Movable AC 5" (127mm) Square Canopy
MSQ_JB	Movable AC 5" (127mm) Square Canopy
WA	Wall Mount
S	Surface Mount



Straight EDGE Joint System



- The Straight EDGE Joint comes standard for all runs.
- Two connection points – one to cinch fixtures together, the other to perfectly align all fixtures in a run.
- Factory-installed light shields on both sides of the fixture ensure no light leaks.
- Patented.

Mounting: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Recessed to Suspended
	Pendant Pipe

Voltage

- Some EX3D configurations will not accommodate all voltage options; consult with factory
- 347 volt not available with Tunable White (TW) option

U	Universal
1	120 volt
2	277 volt
3	347 volt



Driver

- Standard Driver Option = FSD
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more driver options see Pinnacle Resource Guide
- Some EX3D configurations will not accommodate all driver options; consult with factory

0-10V Drivers

FSD	Factory Select Driver 1%, 0-10v
PL2	Signify Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v, requires 347v
OL2	eldoLED Optotronic, 1%, 0-10v
OL4	eldoLED Optotronic 347v, 1% 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0-10v, 0.1% Logarithmic
ES2	eldoLED SOLOdrive 0-10v, 0% Linear
OL5	Advance Xitanium 1%, 0-10v, AUX, Dim to Off
PL5	eldoLED Optotronic 1%, 0-10v, AUX, Dim to Off

DALI Drivers

EE3	eldoLED ECOdrive 1%, DALI 2, Logarithmic, DT6
ES3	eldoLED SOLOdrive 0.1%, DALI 2, Logarithmic, DT6
OD1	eldoLED Optotronic 1%, DEXAL
EE4	eldoLED ECOdrive 1%, DALI 2, Linear, DT6
ES4	eldoLED SOLOdrive 0.1%, DALI 2, Linear, DT6
PR1	Advance Xitanium SR, DALI 2, Self powered link

Lutron Drivers

LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
------------	---

Alternate Drivers

PS1	Signify Advance Xitanium Step Dimming 50%/100%
EH1	ELV 120v only, 0-10v universal

Driver: MOD Options

- Specify **MOD** in the part number for any of the below options
- MOD specifications are subject to longer lead-times. Consult factory for more information

MOD	Power Over Ethernet
------------	---------------------

How to specify Circuiting, Battery and Emergency

1

- Select fixture circuiting from options below
- Some EX3D configurations will not accommodate all circuiting options, consult with factory
- Consult factory for Emergency (E) or Night Light (N) circuit with Tunable White (TW) option

Circuiting

1	Single Circuit
M	Multi Circuit
E	Emergency Circuit only
N	Night Light Circuit only

2

+

3

- Battery and emergency section options are available in addition to fixture circuit
- Select battery and emergency section options below; factory shop drawing required
- Some EX3D configurations will not accommodate all circuiting options, consult with factory

Battery and/or Emergency If Required

0	No battery or specific emergency section required
----------	---



Battery

- Select battery section type if required, indicate total QTY. *Example 2PL*
- 90 minute battery runtime; test button is remote to fixture and requires an additional drop
- No battery option available for 2' lengths
- Entire direct fixture housing is on battery for lengths up to 5'

- Half of direct fixture is on battery for 6' or 8' housing lengths
- For more battery options available, see Pinnacle Resource Guide
- For Tunable White (TW) option, battery will illuminate 6500K LED unless otherwise specified

0	No Battery
_FSB	Factory Select Battery (10w option)
_FSBST	Factory Select Battery (10w, Self Testing)
_PLL	Bodine 10w Integral Lithium, Self Testing
_ILL	Iota 10w Integral Lithium, Self Testing

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 92.3 (LPW) x 10 (watts) = 923 battery lumen output

Emergency

- Select emergency section type if required, indicate total QTY. *Example 1E*
- Combine battery and emergency section ordering codes if both options are selected
- Consult factory for Emergency Control Devices with Tunable White (TW) option

_FSG	Factory Select ALCR Emergency Control Device, UNV
_GI	Iota ETS-DR, Emergency Control Device, UNV
_GB	Bodine GTD, Emergency Control Device, 120v or 277v
_E	Emergency circuit section
_N	Night Light circuit section
_L	Life Safety circuit section NO THROUGH WIRE

Battery OR Emergency Ordering Examples

- | | |
|--|-----------------------|
| • Single circuit, 10w Integral Battery | Ordering Code: 1-1PLL |
| • Emergency only, 10w Integral Battery | Ordering Code: E-1PLL |
| • Single circuit, GTD required | Ordering Code: 1-1GB |

Combination Section Ordering Examples

- | | |
|--|------------------------|
| • Single circuit, (1) 10w battery, (1) emergency section | Ordering Code: 1-1PL1E |
| • Multi circuit, (2) 10w battery, (2) emergency sections | Ordering Code: M-2PL2E |
| • Single circuit, (1) night light section | Ordering Code: 1-1N |

Finish


- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

W	White (<i>white cord/white canopy</i>)
S	Metallic Silver (<i>white cord/silver canopy</i>)
BL	Textured Black (<i>black cord/black canopy</i>)
BR	Bronze (<i>white cord/bronze canopy</i>)
GR	Graphite (<i>white cord/graphite canopy</i>)
CC	Custom Color (<i>white cord/color match canopy</i>)

Fixture Options

- Additional options to enhance the fixture and finish of the product
- Consult factory for MR16 configurations

QS	10 day Quick Ship
TC	Indirect Top Cover (<i>ac mounting only</i>)
LMRA	Adjustable MR16 LED (<i>only available with 120v</i>)
DSP	Customer Supplied Battery/Driver/Sensor
XLED	Fixed Xicato LED



*Cross section with TC Option

Fixture Options: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Remote Driver
	End Power Feed

Quick Ship

Shielding	CRI, CCT & Output	Mounting	Voltage	Driver	Circuiting	Battery	Finish
10-Day							
A HE BW WHE	80 CRI, all color temperatures, all lumen packages <i>See pg 2</i>	(M)AC48G (M)AC48JB (M)AC48ST W S	(M)AC to Grid (M)AC to J-BOX (M)AC to Structure Wall Mount Surface Mount	U Universal (120-277) 1 120V 2 277V	FSD Factory Select Driver (1%, 0-10v) 1 Single Circuit E Emergency N Night Light	0 None _FSB Factory Select Battery	W White S Silver BL Black

All lengths and continuous rows up to 1,000 ft OR 150 individual fixtures. Black QuickShip only available in 4', 6', and 8' individual lengths. Consult factory for larger projects.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

EX3D_LED_SPEC_JUNE2025



Controls

- Pinnacle Lighting offers easy to specify network control solutions that connect to an intelligent centralized system to maximize lighting energy efficiencies or integral sensors for individual fixture control
- Pinnacle Lighting fixtures ship technology ready; commissioning by others
- Controls can only be used with Single Circuit (1) or Emergency Circuit (E)
- Contact factory for any non-standard configurations for layout, placement, or EM options
- One drop per sensor typical, consult factory for more information
- Must specify required driver in Driver Section
- Consult factory for available Controls with Tunable White (TW) option

	Solution	Components	Network/Sensor	Connection	Required Drivers	Limitation
DLMFS	Legrand Wattstopper LLLC	LMFS-601-W / LMFI-111	Wireless DLM Fixture Sensor	Wireless	OD1, PR1 or 0-10v	0-10v requires interface
EASYS	Philips EasySense	SNS-210	Daylight/PIR Occupancy	Wireless to switches	PR1	Not available with 347 volt
SNSLM	Encelium Sensilum	EN-CLM-PIR-DD-ZB	Encelium, Daylight/PIR Occupancy	Wireless	OD1, OL5	Not available with 347 volt
WLVX	Eaton Wavelinx	SWPD1, NSP3IVMVDC1	WaveLinx WCL, Daylight	Wireless	Any 0-10v	Not available with 347 volt
VDO	Lutron Vive Sensor	DFCSJ-OEM-OCC	Vive, Daylight/PIR Occupancy	Wireless	OD1, PR1	Not available with 347 volt
VRF	Lutron Vive Connected	DFCSJ-OEM-RF	Vive	Wireless	OD1, PR1	Not available with 347 volt

Controls: MOD Options


- Specify **MOD** in the part number for any of the below options
- Control** Options may require specific driver. Refer to the chart below
- Consult factory for **MOD** specification details, pricing, and lead-time information

	Required Driver
MOD Encelium Sensilum	OD1, OL5
Enlighted (Wireless) - ENLI	Any 0-10v
Enlighted (Wireless) - ENLC	Any 0-10v
Acuity nLight Air Wireless Connected	EE6, ES6

Photometrics

Satine Lens

Test # 91449, 93985¹
 Catalog # EX3D-A-840VHO-4
 Lumens 4125 lm
 Watts 36 w
 Efficacy 114.6 LPW



Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	1446	1446	1446	1446	1446
5	1439	1440	1440	1440	1440
10	1422	1420	1423	1423	1423
15	1393	1383	1391	1392	1389
20	1347	1338	1346	1346	1344
25	1292	1280	1289	1289	1286
30	1225	1214	1222	1220	1217
35	1149	1137	1146	1141	1138
40	1062	1054	1059	1054	1052
45	969	960	963	958	954
50	865	859	860	854	852
55	756	751	750	743	744
60	641	635	633	629	626
65	522	518	516	511	511
70	399	395	392	391	391
75	276	275	275	274	275
80	161	163	164	164	166
85	67	67	69	69	69
90	0	0	0	0	0

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	11170	11101	10997
55	10744	10658	10573
65	10068	9952	9856
75	8692	8661	8661
85	6266	6453	6453

¹Based on ITL Reports 91449 and 93985.

For all available IES files, please visit our website at pinnacle-ltg.com. Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP accredited testing laboratory. Testing conducted at 25°C ambient conditions.



Applications & Certificates

Construction: 6063-T6 Extruded aluminum housing. Highly reflective steel white painted reflector.

Shielding: Diffuse snap-in acrylic lens, removable for maintenance.

Mounting: Aircraft cable and wall mount available. Select from 2 aircraft cable options. Select the straight aircraft cable that mounts on 4'-0" (1219.2mm) and 8'-0" (2438.4mm) centers or the movable adjustable Y-cable mount. The Y-Cable design allows for adjustable mounting locations. Aircraft Cable supplied with 5" (127mm) power and 2" (50.8mm) non-power canopies. Refer to installation instructions for appropriate ceiling detail. Canopies are painted white unless otherwise specified. Maximum fixture weight is 20 lbs. for a standard 4' fixture.

White LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%; 2' or 3' lengths may have a greater wattage deviation. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. TM-21-21 Lifetime Rating L70 = >72,000 hours, L90 = 69,700 hours. MacAdam 3-Step Ellipses. For all available IES files, please visit our website at pinnacle-ltg.com.

Tunable White LED: 2 channel solution with 2700K and 6500K LED, 90CRI only, R9 >50. Lumen packages available shown at 4000K CCT setpoint, lumen output varies based on CCT. Use multipliers for other CCT; 2700K = .91 3000K = .93 3500K = .97 4000K = 1.0 5000K = 1.044 6500K = 1.078.

CRI, CCT & Output: Not all lumen packages available. Three lumen packages available. Standard, High (HO) and Very High (VHO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K and 4000K. 90 CRI = R9≥50.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify PL4 or OL4 in Driver section when 347 volt (3) is selected. Some EDGE configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Factory Select Driver 0-10V, 1% = FSD. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 122°F/50°C. For more driver options, see Pinnacle Resource Guide. Some EDGE configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Multi circuit (M), Emergency circuit (E) or Night Light circuit (N). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some EX configurations will not accommodate all circuiting options, consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is remote to fixture. For more Battery options, see Pinnacle Resource Guide.

Finish: Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes. Canopies painted white unless specified differently in the options section of the part number. Contact factory for additional custom color and finish options.

MR16: Ideal for conference rooms, corridors, wall washing, retail spaces and training facilities where accent lighting is required. Fully enclosed compartment eliminates light from entering into our fixture areas. LED lamps are not included. Consult factory for other lamp types. Standard 60 watt max LED electronic transformer (120v), MR16 installed as an independent circuit. MR16 to match fixture voltage. LMRA option not available with 277v. Consult factory for MR16 configurations.

Controls: Standard options available, refer to Controls section table for available options, component part number(s), connection type, required driver and limitations. Mod options available, consult with factory.

Labels: ETL listed conforming to UL 1598 in US and CSA 250 in Canada. Standard and HO lumen packages are approved for dry/damp location unless otherwise noted.

Sustainability: All EDGE models are Living Building Challenge (LBC) Declared with third-party verification. The Declare Label from ILFI provides transparent insights into materials, sourcing, and environmental impact, promoting informed, sustainable choices that benefit both people and the planet. View the label [here](#).

Fixture Weight: Maximum fixture weight is 20 lbs. for a standard 4' fixture.

Buy American Act Compliant

Warranty: EX LED offered with a 5-year limited warranty. Covers LED, driver and fixture.