


ADEO AD14

1x4 Architectural Recessed



Key Features

- Formed 20 gauge cold rolled steel housing
- Highly reflective die-formed white painted reflector
- Wiring access available on top of housing
- LED offered with a 5-year limited warranty. Covers LED, driver and fixture
- UL and cUL Listed, LO, MO, and HO lumen packages are IC Rated
- Approved for dry/damp location unless otherwise noted
- Room-Side Maintenance for LED system



Example Part #: AD14-A-830HO-G1-U-FSD-1-0-W

AD14 - SHIELDING - CRI, CCT & OUTPUT - MOUNTING - VOLTAGE - DRIVER - CIRCUITING - BATTERY & EMERGENCY - FINISH - FIXTURE OPTIONS - CONTROLS

SHIELDING	SOURCE ^{Q.S.} 1,2	MOUNTING	VOLTAGE ³
A - Satine Lens ^{Q.S.} R - Round Perf L - Linear Perf <i>Shielding pg. 2</i>	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K TW - 2CH Tunable White (2700-6500K, 90CRI) CL - Custom Lumens CW - Custom Watts MOD - Mod options available <i>Lumen Output pg. 2-3</i>	G1 - 15/16" Grid ^{Q.S.} G9 - 9/16" Grid ^{Q.S.} GS - Screw Slot Grid ^{Q.S.} FL - Flanged S - Surface Mount <i>Mounting pg. 3</i>	U - Universal (120 thru 277V) ^{Q.S.} 1 - 120V ^{Q.S.} 2 - 277V ^{Q.S.} 3 - 347V <i>Voltage pg. 3</i>
DRIVER	CIRCUITING ⁴	BATTERY & EMERGENCY	FINISH
FSD - Factory Select Driver (1%, 0-10v) ^{Q.S.} PL2 - Advance Xitanium (1%, 0-10v) OL2 - eldoLED Optotronic (1%, 0-10v) OL4 - eldoLED Optotronic 347v (1%, 0-10v) EE1 - eldoLED ECOdrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0.1%, 0-10v) LH1 - Lutron Hi-lume (1%, EcoSystem) PS1 - Advance Xitanium (50%/100%) MOD - Mod options available <i>Driver pg. 4</i>	1 - Single Circuit ^{Q.S.} E - Emergency (entire fixture) ^{Q.S.} N - Night Light (entire fixture) ^{Q.S.} <i>Circuiting pg. 4</i>	0 - None ^{Q.S.} FSB - Factory Select Battery ^{Q.S.} FSG - Factory Select ALCR GI - Iota ETS DR GB - Bodine GTD 1IC - Iota 10W, CEC Listed 1P - Bodine 10W ^{Q.S.} <i>Battery and Emergency pg. 4</i>	W - White ^{Q.S.} MOD - Mod options available <i>Finish pg. 5</i>
FIXTURE OPTIONS ⁵	CONTROLS		
QS - QuickShip ^{Q.S.} TW - Through-wiring CP - Chicago Plenum ^{Q.S.} AM - Antimicrobial Paint AR - Air Return FW6 - 6' Flex Whip ^{Q.S.} GLR - Fast Blow Fusing DSP - Customer Supplied Battery/Driver/ Sensor GMF - Slow Blow Fusing MOD - Mod options available <i>Fixture Options pg. 5-6</i>	MOD - Mod options available <i>Controls pg. 6</i>		


¹When specifying SOURCE the first _ is for specifying either 8 - 80CRI, 9 - 90CRI. The ending _ _ are for specifying output, example 835HO - 80CRI, 3500K High Output. See output charts for more information. ²When specifying Tunable White, use **TW** and then specify output, example TWHO - Tunable White 90CRI, High Output 2700-6500K. See output charts for more information. Tunable White option requires driver option **FSD** which provides separate 0-10v control leads for Intensity and CCT. ³Tunable White (**TW**) option only available with Universal (**U**), 120V (**1**) or 277V (**2**) options. ⁴Consult factory for Emergency (**E**) or Night Light (**N**) options with Tunable White option. ⁵If specifying QuickShip, **QS** must be used in fixture options section of part number to qualify.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Shielding

- Captive and hinged center lens
- Co-extruded acrylic lens with ribbed side channels evenly illuminates the side reflector giving the appearance of a fully lensed luminaire
- Highly reflective die-formed white painted reflector
- Wiring access available on top of housing



Output

- Specify either 80 or 90 CRI for White light LED
- Longer lead-time may apply for 90 CRI or Tunable White option. Consult factory
- Tunable White option requires driver option FSD which provides separate 0-10v control leads for Intensity and CCT.
- Tunable White lumen packages shown at 4000K CCT setpoint
- 90 CRI = R9≥50

Custom Output- Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL8351200)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW _____	Specify CRI, CCT and desired wattage (i.e. CW94015)	Specify watts between standard offering listed below
CLTW _____	Specify desired lumens for Tunable White (i.e. CLTW3200)	Specify lumens between Tunable White offering listed below. Lumens are specified at 4000K CCT setpoint.

80 CRI

	Color	Output	Watts	Shielding					
				A		L		R	
				Satine Lens		Linear Slot		Round Perf	
				Lumens	LPW	Lumens	LPW	Lumens	LPW
830LO	3000K	Low	15.6	2201	141	1307	84	1118	72
830MO		Middle	23.7	3303	139	1962	83	1678	71
830HO		High	33.4	4577	137	2718	81	2325	70
835LO	3500K	Low	15.6	2210	142	1313	84	1123	72
835MO		Middle	23.7	3317	140	1970	83	1685	71
835HO		High	33.4	4596	138	2730	82	2335	70
840LO	4000K	Low	15.6	2269	145	1348	86	1153	74
840MO		Middle	23.7	3406	144	2023	85	1730	73
840HO		High	33.4	4719	141	2803	84	2397	72

90 CRI

927LO	2700K	Low	15.6	1825	117	1084	69	927	59
927MO		Middle	23.7	2739	116	1627	69	1391	59
927HO		High	33.4	3795	114	2254	67	1928	58
930LO	3000K	Low	15.6	1869	120	1110	71	950	61
930MO		Middle	23.7	2806	118	1666	70	1425	60
930HO		High	33.4	3888	116	2309	69	1975	59
935LO	3500K	Low	15.6	1951	125	1159	74	991	64
935MO		Middle	23.7	2928	124	1739	73	1487	63
935HO		High	33.4	4057	121	2410	72	2061	62
940LO	4000K	Low	15.6	2003	128	1189	76	1017	65
940MO		Middle	23.7	3006	127	1785	75	1527	64
940HO		High	33.4	4165	125	2474	74	2116	63

2 CH Tunable White (2700-6500K, 90CRI)

TWLO	2700 - 6500K	Low	20.9	2200	105.5	1330	63.8	1138	54.5
TWMO		Middle	31.5	3300	104.8	1960	62.3	1676	53.2
TWHO		High	45.1	4500	99.8	2724	60.4	2330	51.7

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568



Direct Source: MOD Options











- Specify **MOD** in the part number for any of the below options
- All RGB_ Source Options will require specific driver and control

- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD		RQD Driver	RQD Control
	Color Changing RGB LED	EC1	DMX
	Color Changing RGB-W LED	EC1	DMX
	Dynamic BIOS		

Mounting

- Designed to install into acoustical grid and inaccessible ceilings
- Grid retention clips integral to housing and require mechanical attachment
- Tie off fixture to structure with retention wires
- Maximum fixture weight is 15 lbs - Surface Mount Box adds 10 lbs
- Refer to installation instructions during installation at the job site
- Approved for dry/damp location unless otherwise noted

G1	G9	GS	FL	S
1" Grid Mount <i>Works with 15/16" grid ceiling types. See profile for fixture position in relation to ceiling grid and tile.</i>	9/16" Grid Mount <i>Works with 9/16" grid ceiling type. For tegular tile installations, fixture position will not be flush to the bottom of the tile. See tegular tile profile image below.</i>	Screw Slot Mounting <i>Works with screw slot, bolt slot and 9/16" grid ceiling types. For 9/16" installations with tegular tile, fixture position will be flush to the bottom of the tile. See bottom profile image of 9/16" with tegular tile. Consult factory for detailed installation instructions.</i>	Flange Kit <i>A separate flange kit is supplied for installations into inaccessible or drywall applications. Flange kit ships from factory uninstalled separately from fixture. Consult factory for detailed installation instructions.</i>	Surface Mount <i>Utilize for hard lid ceiling applications. The 20 gauge steel frame easily secures to ceiling.</i>
 <p>Standard Tile</p>  <p>Tegular Tile</p>	 <p>Standard Tile</p>  <p>Tegular Tile</p>	 <p>Tegular Tile</p>  <p>Tegular Tile</p>	 	 <p>3-1/8" (80.3mm)</p> 

Voltage

- Some ADEO configurations will not accommodate all voltage options; consult with factory
- 347 volt not available with Tunable White (TW) option

U	Universal
1	120 volt
2	277 volt
3	347 volt



Driver

- Standard Driver Option = FSD
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more Driver options, see Pinnacle Resource Guide
- Some ADEO configurations will not accommodate all driver options; consult with factory

0-10V Drivers	
FSD	Factory Select Driver 1%, 0-10v
PL2	Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v, requires 347v
OL2	eldoLED Optotronic, 1%, 0-10v
OL4	eldoLED Optotronic 347v, 1% 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v, Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v, Linear
ES1	eldoLED SOLOdrive 0.1%, 0-10v, Logarithmic
ES2	eldoLED SOLOdrive 0.1%, 0-10v, Linear
OL5	eldoLED Optotronic 1%, 0-10v, AUX , Dim to Off
PL5	Advance Xitanium 1%, 0-10v, AUX, Dim to Off
DALI Drivers	
EE3	eldoLED ECOdrive 1%, DALI 2, Logarithmic, DT6
ES3	eldoLED SOLOdrive 0.1%, DALI 2, Logarithmic, DT6
OD1	eldoLED Optotronic 1%, DEXAL, DALI 2, DT6, Self powered link
PR1	Advance Xitanium SR, DALI 2, Self powered link
Lutron Drivers	
LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
Alternate Drivers	
PS1	Advance Xitanium Step Dimming 50%/100%
EH1	ERP 1%, Line Voltage and ELV, requires 120v

Drivers: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Power Over Ethernet
------------	---------------------

Circuiting

- Select fixture circuiting from options below
- Some ADEO configurations will not accommodate all circuiting options; consult with factory
- Consult factory for Emergency (E) of Night Light (N) circuit with Tunable White (TW) option

1	Single Circuit
E	Emergency Circuit only
N	Night Light Circuit only



Battery & Emergency

- Select battery or emergency options if required
- Battery duration is 90 minutes
- For Tunable White (TW) option battery with illuminate 6500K LED unless otherwise specified
- Test button is integral to fixture
- For more Battery options, see Pinnacle Resource Guide
- Consult factory for Emergency Control Devices with Tunable White (TW) option

0	No Battery
FSB	Factory Select Battery (10w option)
FSBST	Factory Select Battery (10w, Self Testing)
FSG	Factory Select ALCR Emergency Control Device, UNV
GI	Iota ETS-DR, Emergency Control Device, UNV
GB	Bodine GTD, Generator Transfer Device, 120v or 277v
1ILL	Iota 10w Integral Lithium, Self Testing
1PLL	Bodine 10w Integral Lithium, Self Testing

Battery & Emergency Ordering Examples

- Single circuit, 10w integral battery Ordering Code: 1-1FSB
- Emergency circuit only, 10w integral battery Ordering Code: E-1FSB

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 10 (watts) x 92.3 (LPW) = 923 battery lumen output

Finish

- Powder-coat white painted finish on exposed trim

W	White
----------	-------

Finish: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Wood Grain
	Metallic Silver
	Textured Black
	Bronze
	Graphite
	Custom Color
	Natural

Fixture Options

- Additional options to enhance the fixture and finish of the product

QS	Quick Ship
TW	Through-Wiring
CP	Chicago Plenum
AM	Antimicrobial Paint
AR	Air Return
FW6	Flex Whip 6'
GLR	Internal Fast Blow Fuse
DSP	Customer Supplied Battery/Driver/Sensor
GMF	Internal Slow Blow Fuse

Fixture Options: MOD Options

- Specify **MOD** in the part number for any of the below options
- Consult factory for **MOD** specification details, pricing, and lead-time information

MOD	Remote Driver
	End Power Feed



Quick Ship

	CRI, CCT & Output	Mounting	Voltage	Driver	Circuiting	Battery	Finish	Options
10-Day								
A	80 CRI, All color temperatures, all lumen packages <i>See pg 4&5</i>	G1 1" Grid G9 9/16" Grid GS Screw Slot	U Universal 1 120V 2 277V	FSD Factory Select Driver (7%, 0-10V)	1 Single E Emergency N Night Light	0 None FSB Factory Select Battery	W White	CP Chicago Plenum FW6 Flex Whip 6' GLR 18-gauge Internal Fast-Blow Fuse

Consult Factory for projects that are larger than 200 units.

Controls

- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

Controls: MOD Options


- Specify **MOD** in the part number for any of the below options
- Control** Options may require specific driver. Refer to the chart below
- Consult factory for **MOD** specification details, pricing, and lead-time information

	Ordering Code	Required Driver
MOD Wattstopper PLUS SensiLUM	SNSLM	OD1, OL5
Lutron Athena Sensor	AWNS	OD1, PR1, OL5, PL5
Lutron Athena Connected	AWNCR	OD1, PR1, OL5, PL5

Photometrics

Satine Lens

Test #	ITL88948
Catalog #	AD14A-840MO
Lumens	3331 lm
Watts	26 W
Efficacy	128 LPW



Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	1121	1121	1121	1121	1121
5	1115	1116	1116	1117	1117
10	1100	1099	1103	1104	1103
15	1074	1071	1080	1084	1082
20	1039	1034	1047	1053	1053
25	993	988	1006	1014	1015
30	938	936	956	967	968
35	876	876	898	912	916
40	806	810	835	851	855
45	731	739	765	781	787
50	651	663	690	707	715
55	567	581	609	628	637
60	480	497	525	545	555
65	390	409	438	458	466
70	299	320	347	364	373
75	210	231	252	264	265
80	125	143	156	169	173
85	55	63	75	85	85
90	0	0	0	0	0

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	3062	3204	3296
55	2928	3145	3289
65	2733	3069	3266
75	2403	2884	3032
85	1869	2549	2888



Applications & Certificates

Construction: Formed 20 gauge cold rolled steel housing. Highly reflective die-formed white painted reflector. Wiring access available on top of housing. Captive and hinged center lens swings open for room-side maintenance of lens, driver and LED boards.

Shielding: Co-extruded acrylic lens with ribbed side channels evenly illuminates the side reflector giving the appearance of a fully luminous aperture. Available with standard satine lens or optional clear lens with linear slot or round perf insert.

Mounting: Designed to install into acoustical grid and inaccessible ceilings. Specify G1, G9 or GS for acoustical grid ceiling. Specify FL for inaccessible ceilings. Grid retention clips integral to housing and require mechanical attachment. Tie off fixture to structure with retention wires.

White LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 123,100 hours and L90 = 36,700 hours. MacAdam 3-Step Ellipses. Not all products are lighting facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

Tunable White LED: 2 channel solution with 2700K and 6500K LED, 90CRI only, R9 >50. Lumen packages available shown at 4000K CCT setpoint, lumen output varies based on CCT. Use multipliers for other CCT; 2700K = .91 3000K = .93 3500K = .97 4000K = 1.0 5000K = 1.044 6500K = 1.078.

CRI, CCT & Output: Four lumen packages available. Low (LO), Medium (MO), High (HO) and Very High (VHO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on Color Temperature & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 90 CRI = R9≥50.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL4 in Driver section when 347 volt (3) is selected. Some ADEO configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Advance Xitanium 0-10V, 1% = PL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 91°F/33°C. For more driver options, see Pinnacle Resource Guide. Some ADEO configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). Some ADEO configurations will not accommodate all circuiting options, consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is integral to fixture. For more Battery options, see Pinnacle Resource Guide.

Finish: Powder-coat white painted finish on exposed trim.

Controls: Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

Labels: UL and cUL 1598 listed. LO, MO, HO and VHO lumen packages are IC Rated, approved for dry/damp location unless otherwise noted.

Fixture Weight: 15 lbs maximum - Surface mount box adds 10 lbs

Warranty: ADEO LED offered with a 5-year limited warranty. Covers LED, driver and fixture.