


LiFT LF44

4x4 Direct Recessed Architectural Square



Key Features

- Formed 20 gauge cold rolled steel housing
- Highly reflective die-formed white painted reflector
- Fabricated, captive lens with 3 lens positions
- LiFT offered with a 5-year limited warranty. Covers LED, driver and fixture
- ETL Listed conforming to UL1598 in US and CSA 250 in Canada
- Room-Side Maintenance for LED system



Example Part #: LF44-AR-930HO-G-U-FSD-1-0-W

LF44 - AR - SHIELDING - CRI, CCT & OUTPUT - MOUNTING - VOLTAGE - DRIVER - CIRCUITING - BATTERY & EMERGENCY - FINISH - FIXTURE OPTIONS - CONTROLS

AR	-----	-----	---
SHIELDING	SOURCE^{1,2}	MOUNTING	VOLTAGE³
AR - Regressed Satine Lens	_27_ - 2700K _30_ - 3000K _35_ - 3500K _40_ - 4000K TW - 2CH Tunable White (2700-6500K, 90CRI) CL - Custom Lumens CW - Custom Watts <i>Source pg. 2</i>	G - Grid Ceiling FL - Flanged SF - Spackle Flange <i>Mounting pg. 2</i>	U - Universal (120 thru 277V) 1 - 120V 2 - 277V 3 - 347V <i>Voltage pg. 3</i>
---	---	---	---
DRIVER	CIRCUITING⁴	BATTERY & EMERGENCY	FINISH
FSD - Factory Select Driver (1%, 0-10v) PL2 - Advance Xitanium (1%, 0-10v) OL2 - eldoLED Optotronic (1%, 0-10v) OL4 - eldoLED Optotronic 347v (1%, 0-10v) EE1 - eldoLED ECOdrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0.1%, 0-10v) LH1 - Lutron Hi-lume (1%, EcoSystem) PS1 - Advance Xitanium (50%/100%) <i>Driver pg. 3</i>	1 - Single Circuit E - Emergency (entire fixture) <i>Circuiting pg. 3</i>	0 - None FSB - Factory Select Battery FSG - Factory Select ALCR GI - Iota ETS DR GB - Bodine GTD 1ILL - Iota 10w 1PLL - Bodine 10w <i>Battery and Emergency pg. 4</i>	W - White <i>Finish pg. 4</i>
---	---	---	---
FIXTURE OPTIONS⁵	CONTROLS		
CP - Chicago Plenum AM - Antimicrobial Paint FW6 - 6' Flex Whip DSP - Customer Supplied Battery/Driver/Sensor GMF - Slow Blow Fusing BA - Buy America(n) Act and/or Build America Buy America Compliant <i>Fixture Options pg. 4</i>	MOD - Mod options available <i>Controls pg. 4</i>		

¹When specifying SOURCE the ending _ are for specifying output, example **HO** - High Output. See output charts for more information. ²When specifying Tunable White, use TW and then specify output, example **TWHO** - Tunable White 90CRI, High Output 2700-6500K. See output charts for more information. Tunable White option requires driver option FSD which provides separate 0-10v control leads for Intensity and CCT. ³Tunable White (TW) option only available with Universal (U), 120V (1) or 277V (2) options. ⁴Consult factory for Emergency (E) options with Tunable White (TW) option. ⁵Compliance is configuration dependent; consult factory for confirmation.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Source

- 90 CRI = R9≥50
- Longer lead-time may apply for Tunable White option. Consult factory
- Tunable White option requires driver option FSD which provides separate 0-10v control leads for Intensity and CCT.
- Tunable White lumen packages shown at 4000K CCT setpoint

Custom Output- Lumens OR Wattage

CL _____	Specify CCT and desired lumens (i.e. CL9352000)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW _____	Specify CCT and desired wattage (i.e. CW94020)	Specify watts between standard offering listed below
CLTW _____	Specify desired lumens for Tunable White (i.e. CLTW3200)	Specify lumens between Tunable White offering listed below. Lumens are specified at 4000K CCT setpoint.

90 CRI









	Color	Lumens	Shielding AR Satine Lens Watts	LPW
927LO	2700K	9804	75.9	129
927MO		15939	130.9	122
927HO		21806	191.0	114
930LO	3000K	10255	76.0	135
930MO		16647	130.7	127
930HO		22791	191.0	119
935LO	3500K	10046	75.7	133
935MO		16300	130.0	125
935HO		22443	191.6	117
940LO	4000K	10377	75.5	137
940MO		16835	129.5	130
940HO		23214	191.1	121

2 CH Tunable White (2700-6500K, 90CRI)

TWLO	2700 - 6500K	9800	87.1	113
TWMO		16500	155.4	106
TWHO		21700	212.1	102

Mounting

- Designed to install into acoustical grid and inaccessible ceilings
- Grid retention clips integral to housing and require mechanical attachment
- Tie off fixture to structure with retention wires
- Maximum fixture weight is 94 lbs
- Refer to installation instructions during installation at the job site
- Approved for dry/damp location unless otherwise noted

G		FL		SF
1" Grid Mount <i>Works with 15/16" grid ceiling types. See profile for fixture position in relation to ceiling grid and tile.</i>	9/16" Grid Mount <i>Works with 9/16" grid ceiling type. For regular tile installations, fixture position will be flush to the bottom of the tile. See regular tile profile image below.</i>	Screw Slot Mounting <i>Works with screw slot and bolt slot ceiling types.</i>	Flange <i>Utilize in drywall application when a flange is required.</i>	Spackle Flange <i>Utilize in drywall application when a flangeless look is required.</i>
 <p>Standard Tile</p>	 <p>Standard Tile</p>	 <p>Tegular Tile</p>		
 <p>Tegular Tile</p>	 <p>Tegular Tile</p>	<div> Side-by-Side Installation LIFT has the ability to have 2 fixtures mounted side by side using the same grid. This detail allows LIFT to be installed in a pattern with only the space of the T-bar between the fixtures.  </div>		

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

LF44_RECESSED_SPEC_SEPTEMBER2025



Voltage

- Some LIFT configurations will not accommodate all voltage options; consult with factory
- 347 volt not available with Tunable White (TW) option

U	Universal
1	120 volt
2	277 volt
3	347 volt

Driver

- Standard Driver Option = FSD
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more Driver options, see Pinnacle Resource Guide on download pages at pinnacle-ltg.com
- Some LIFT configurations will not accommodate all driver options; consult with factory

0-10V Drivers	
FSD	Factory Select Driver 1%, 0-10v
PL2	Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v, requires 347v
OL2	eldoLED Optotronic 1%, 0-10v
OL4	eldoLED Optotronic 347v, 1% 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0-10v, 0.1% Logarithmic
ES2	eldoLED SOLOdrive 0-10v, 0% Linear
DALI Drivers	
EE3	eldoLED ECOdrive 1%, DALI 2, Logarithmic, DT6
ES3	eldoLED SOLOdrive 0.1%, DALI 2, Logarithmic, DT6
OD1	eldoLED Optotronic 1%, DEXAL
Lutron Drivers	
LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
Alternate Drivers	
PS1	Advance Xitanium Step Dimming 50%/100%

Circuiting

- Select fixture circuiting from options below
- Some LIFT configurations will not accommodate all circuiting options; consult with factory

1	Single Circuit
E	Emergency Circuit only



Battery & Emergency

- Select battery or emergency options if required
- Battery duration is 90 minutes
- Test button is integral to fixture

- For more Battery options, see Pinnacle Resource Guide on download pages at pinnacle-ltg.com

0	No Battery
FSB	Factory Select Battery (10w option)
FSBST	Factory Select Battery (10w, Self Testing)
FSG	Factory Select ALCR Emergency Control Device, UNV
GI	Iota ETS-DR, Emergency Control Device, UNV
GB	Bodine GTD, Emergency Control Device, 120v or 277v
1ILL	Iota 10w, Integral Lithium, Self Testing
1PLL	Bodine 10w, Integral Lithium, Self Testing

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 10 (watts) x 129 (LPW) = 1,290 battery lumen output

Battery & Emergency Ordering Examples

- Single circuit, 10w integral battery Ordering Code: 1-1FSB
- Emergency circuit only, 10w integral battery Ordering Code: E-1PLL

Finish

- Powder-coat white painted finish on exposed trim
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

W	White
----------	-------

Fixture Options

- Additional options to enhance the fixture and finish of the product

CP	Chicago Plenum
AM	Antimicrobial Paint
FW6	Flex Whip 6'
DSP	Customer Supplied Battery/Driver/Sensor
GMF	Internal Slow Blow Fuse

- Domestic content option - compliance is configuration dependent; consult factory for conformation

BA	Buy America(n) Act and/or Build America Buy America Compliant
-----------	---

Controls

- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

Controls: MOD Options

- Specify **MOD** in the part number for any of the below options
- **Control** Options may require specific driver. Refer to the chart below

- Consult factory for **MOD** specification details, pricing, and lead-time information


MOD	Ordering Code	Required Driver
Lutron Athena Connected	AWNRR	OD1, PR1, OL5, PL5



Photometrics

Satine Lens

Test # SCALED FROM KPL2015-109
Catalog # LF44-AR-940HO
Lumens 28361 lm
Watts 234 watts
Efficacy 121 LPW



Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	10994	10994	10994	10994	10994
5	10937	10919	10895	10900	10907
10	10712	10687	10661	10670	10684
15	10367	10332	10302	10316	10338
20	9910	9870	9840	9859	9889
25	9368	9319	9284	9310	9344
30	8750	8694	8656	8684	8731
35	8073	8009	7973	8003	8055
40	7344	7279	7237	7268	7323
45	6578	6513	6476	6503	6564
50	5787	5720	5690	5711	5773
55	4981	4916	4881	4906	4963
60	4167	4104	4073	4099	4157
65	3360	3298	3270	3294	3349
70	2562	2509	2481	2505	2560
75	1787	1740	1721	1741	1787
80	1059	1021	1010	1024	1058
85	395	387	389	388	400
90	18	17	16	15	13

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6256	6158	6242
55	5839	5723	5818
65	5347	5203	5329
75	4642	4472	4644
85	3046	3002	3084

For all available IES files, please visit our website at pinnacle-ltg.com. Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP or IAS accredited testing laboratory. Testing conducted at 25°C ambient conditions

Approvals & Certifications

Construction: Formed 20 gauge cold rolled steel housing. Highly reflective die-formed white painted reflector. Wiring access available on top of housing. Lens is removable for room-side maintenance of lens, driver and LED boards.

Shielding: Single piece extruded diffuse acrylic lens creating a fully luminous fixture.

Mounting: Designed to install into acoustical grid and inaccessible ceilings. Specify G for acoustical grid ceiling. Specify FL or SF for inaccessible ceilings. Grid retention clips integral to housing and require mechanical attachment. Tie off fixture to structure with retention wires.

White LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. TM-21-21 Lifetime Rating L70 = >60,000 hours, L90 = 52,600 hours. MacAdam 3-Step Ellipses. For all available IES files, please visit our website at pinnacle-ltg.com.

Tunable White LED: 2 channel solution with 2700K and 6500K LED, 90CRI only, R9 >50. Lumen packages available shown at 4000K CCT setpoint, lumen output varies based on CCT. Use multipliers for other CCT; 2700K = .91 3000K = .93 3500K = .97 4000K = 1.0 5000K = 1.044 6500K = 1.078.

Color & Lumen Output: Not all lumen packages available. Three lumen packages available. Low (LO), Medium (MO) and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 90 CRI is available for 2700K, 3000K, 3500K and 4000K. 90 CRI = R9≥50.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify PL4 or OL4 in Driver section when 347 volt (3) is selected. Some configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Factory Select Driver 0-10V, 1% = FSD. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 87°F/26°C. For more driver options, see Pinnacle Resource Guide. Some configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1) or Emergency circuit (E). Some LIFT configurations will not accommodate all circuiting options; consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is integral to fixture. For more Battery options, see Pinnacle Resource Guide on download pages at pinnacle-ltg.com.

Finish: Powder-coat white painted finish on exposed trim.

Controls: Mod options available, consult with factory.

Buy America Act (BAA) and Build America, Buy America Act (BABA) Compliance: BAA and/or BABA compliance options are available to support federally funded projects requiring domestic content. Availability depends on configuration; Compliance is configuration-dependent; consult factory for confirmation.

Labels: UL and cUL 1598 listed. LO, MO, and HO lumen packages are IC Rated, approved for dry/damp location unless otherwise noted.

Fixture Weight: 94 lbs maximum.

Warranty: LIFT LED offered with a 5-year limited warranty. Covers LED, driver and fixture.