

VERBENA V3

3" Suspended Direct or Indirect Linear



Indirect Orientation

Specification Features

- Triangular lens form factor with 145LPW direct or 165LPW indirect widespread illumination
- Enhanced lighting pattern with 6% contribution past nadir
- Minimalistic profile with overall height less than 1 1/2" with triangular lens
- Integral suspension and power cable with singular adjustment mechanism
- Triangular lens form factor with up to 2000lm/ft or 2300lm/ft indirect widespread illumination
- Milled X, T, Y, 90°, 120°, 135° connectors, and a direct-to-indirect alternating joint



Example Part #: V3D-A-830HO-26'-CAC48JB-U-FSD-1-0-W

V3_	SHIELDING	CRI, CCT & OUTPUT	LENGTH OR PATTERN	MOUNTING	VOLTAGE	DRIVER	CIRCUITING	BATTERY & EMERGENCY	FINISH	FIXTURE OPTIONS
-----	-----------	-------------------	-------------------	----------	---------	--------	------------	---------------------	--------	-----------------

V3_	SHIELDING	CRI, CCT & OUTPUT ¹	LENGTH OR PATTERN ²
V3D - VerbenA 3 Direct V3I - VerbenA 3 Indirect <i>Housing pg. 2</i>	A - Satine Lens WS - Widespread Lens <i>Shielding pg. 2</i>	_27_ - 2700K _30_ - 3000K _35_ - 3500K _40_ - 4000K CL - Custom Lumens CW - Custom Watts <i>Lumen Output pg. 2</i>	_ - Individual Fixture _ - Continuous Row S - Square H - Hexagon O - Octagon R - Rectangle L - L-Shape U - U-Shape Y - Y-Shape T - T-Shape X - X-Shape <i>Length and Pattern pg. 2-3</i>
<i>Use page 7 to draw out the pattern.</i>			

MOUNTING ³	VOLTAGE	REMOTE DRIVER	CIRCUITING
CAC - Conductive AC to Grid CAC - Conductive AC to J Box WA - Wall Mount (<i>Direct only</i>) S - Surface Mount (<i>Direct only</i>) <i>Mounting pg. 3</i>	U - Universal (120 thru 277V) 1 - 120V 2 - 277V 3 - 347V <i>Voltage pg. 4</i>	FSD - Factory Select Driver (1%, 0-10v) PL2 - Advance Xitanium (1%, 0-10v) OL2 - eldoLED Optotronic (1%, 0-10v) OL4 - eldoLED Optotronic 347v (1%, 0-10v) EE1 - eldoLED ECOdrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0.1%, 0-10v) LH1 - Lutron Hi-lume (1%, EcoSystem) <i>Driver pg. 4</i>	1 - Single Circuit E - Emergency (<i>entire fixture</i>) N - Night Light (<i>entire fixture</i>) <i>Circuiting pg. 4</i>


BATTERY & EMERGENCY ⁴	FINISH	FIXTURE OPTIONS ⁵	CONTROLS
0 - None _FSB - Factory Select Battery _FSG - Factory Select ALCR _GI - Iota ETS DR _ILL - Iota 10W _PLL - Bodine 10W _E - Emergency Section _N - Night Light Section <i>Battery and Emergency pg. 5</i>	W - White S - Metallic Silver BL - Textured Black BR - Bronze GR - Graphite CC - Custom Color <i>Finish pg. 5</i>	BA - Buy America(n) Act and/or Build America Buy America Compliant <i>Fixture Options pg. 5</i>	<i>Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.</i>

¹When specifying CRI, CCT & OUTPUT the first _ is for specifying either 8 - 80CRI or 9 - 90CRI. The ending _ _ are for specifying output, example **HO** - High Output. See output charts for more information. ²Individual fixtures come in 2', 3', 4', 5', 6', 7', & 8' lengths. Continuous row comes in 1' increments. When specifying patterns specified length will be fixture length. Patterns will be longer than specified length. ³Specify CAC length standard CAC is 48" Example: CAC48JB. Specify grid: G1=15/16", G9=9/16", GS=Screw Slot. Example: CAC48G1. Connectors are not available with **S** - Surface mount, or **WA** - Wall mount options. ⁴Enter quantity for Battery and Emergency, Example 1PLL. ⁵Compliance is configuration dependent; consult factory for confirmation.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Shielding



Output

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory.
- 90 CRI = R9≥50

Custom Output - Lumens OR Wattage

CL_____	Specify CRI, CCT and desired lumens (i.e. CL835500)	Total Max lumens: A Lens- 2,044, WS Lens- 2,312. Max lumens dependant on color temp. Consult factory for more information
CW_____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Total Max watts: 14.8. Consult factory for more information

80 CRI

	Color	Output	Lumens per foot	Shielding A		WS	
				Satine Lens		Widespread Lens	
				LPW	Watts/ft	LPW	Watts/ft
830LO	3000K	Low	500	142	3.5	161	3.1
830MO	3000K	Medium	750	141	5.3	160	4.7
830HO	3000K	High	1000	141	7.1	158	6.3
835LO	3500K	Low	500	146	3.4	164	3.0
835MO	3500K	Medium	750	145	5.2	164	4.6
835HO	3500K	High	1000	145	6.9	163	6.1
840LO	4000K	Low	500	148	3.4	167	3.0
840MO	4000K	Medium	750	147	5.1	167	4.5
840HO	4000K	High	1000	146	6.9	166	6.0

90 CRI

927LO	2700K	Low	500	115	4.3	131	3.8
927MO	2700K	Medium	750	114	6.6	130	5.8
927HO	2700K	High	1000	113	8.8	129	7.8
930LO	3000K	Low	500	119	4.2	136	3.7
930MO	3000K	Medium	750	118	6.4	134	5.6
930HO	3000K	High	1000	117	8.5	134	7.5
935LO	3500K	Low	500	121	4.1	138	3.6
935MO	3500K	Medium	750	120	6.3	136	5.5
935HO	3500K	High	1000	119	8.4	136	7.3
940LO	4000K	Low	500	125	4.0	142	3.5
940MO	4000K	Medium	750	123	6.1	140	5.3
940HO	4000K	High	1000	122	8.2	140	7.1

Length

- All individual units cannot be joined, end plates are factory installed and cannot be removed
- End caps add 2-1/2" (1-1/4" per end) to the overall length of the fixture/row, end caps do not add to mounting distance
- For patterns, refer to Pattern section on next page

2	3	4	5	6	7	8	—
Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Cont. Run Specify nominal overall row length to the 1'
24" (609.6mm)							
	36" (914.4mm)						
		48" (1219.2mm)					
			60" (1524mm)				
				72" (1828.8mm)			
					84" (2133.6mm)		
						96" (2438.4mm)	
							Specify to the 1' >>>

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

V3_LED_SPEC_SEPTEMBER2025




Patterns

- Specify pattern shape and requested fixture length
- Length specified will not reflect overall pattern dimensions
- Angles and shapes not shown require Mod Pattern; consult factory
- All connectors are NON ILLUMINATED
- Minimum length for any single part of a pattern is 2'
- All lengths are TO THE FOOT ONLY

- Driver/Battery Count dictated by product configuration
- Some connectors require longer lead-times. Angles and Shapes not shown require Mod Pattern; Consult Factory.
- Example part number: V3D-A-835HO-Y8x6x8-AC48JB-U-FSD-1-0-GR see resource guide for more information
- Patterns cannot be used with S or WA mounting

S_	H_	O_	R x	U x x	L x	Y x x	T x x	X x x x	MOD
Square Provide A dimension Example: S4'	Hexagon Provide A dimension Example: H4'	Octagon Provide A dimension Example: O4'	Rectangle Provide AxB dimensions Example: R4'x4'	U-Shape Provide AxBxC dimensions Example: U3'x4'x3'	L-Shape Provide AxB dimensions Example: L3'x3'	Y-Shape Provide AxBxC dimensions Example: Y3'x3'x3'	T-Shape Provide AxBxC dimensions Example: T3'x5'x3'	X-Shape Provide AxBxCxD dimensions Example: X2'x5'x2'x5'	Multi Connector Layout For patterns other than shown, factory drawing and sign off required with all MODS

Non-illuminated Connector Details



Mounting


- Specify cable length in ordering code (CAC48JB)
- Adjustable cable. Specify 48", 120", 240", or 350"
- End plates attached at factory
- Canopies and mounts match fixture finish. See Finish section for additional details.

- Approved for dry/damp location unless otherwise noted
- Refer to installation instructions during installation at the job site
- Maximum fixture weight is 10 lbs for a standard 4' fixture
- Driver/Battery Count dictated by product configuration



CAC __ G	Conductive AC to Grid (specify grid type: G1, G9, GS)
CAC __ JB	Conductive AC to Junction Box
WA	Wall Mount (Direct Only, ADA compliant, no patterns)
S	Surface Mount (Direct Only, no patterns)

CAC Canopy Details

- CAC is an integrated power and suspension cable that is smaller in diameter than a traditional SJT cable. CAC is 2 conductive cables and suspension, standard power cable (SJT) is 5 conductive cables and no suspension.



- A larger power side canopy allows for adjustability of the CAC cable inside of the canopy.





Voltage


- Some VERBENA configurations will not accommodate all voltage options; consult with factory

U	Universal
1	120 volt
2	277 volt
3	347 volt

Remote Driver

- Driver/Battery Count dictated by product configuration
- Standard Driver Option = FSD
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more driver options, see Pinnacle Resource Guide
- Some VERBENA configurations will not accommodate all driver options; consult with factory
- All configurations with no PLL, ILL or Emergency Control Device options will use Slim Remote Box

Slim Remote Box



0-10V Drivers

FSD	Factory Select Driver (1%, 0-10v)
PL2	Signify Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v, requires 347v
OL2	eldoLED Optotronic, 1%, 0-10v
OL4	eldoLED Optotronic 347v, 1% 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0-10v, 0.1% Logarithmic
ES2	eldoLED SOLOdrive 0-10v, 0% Linear

DALI Drivers

EE3	eldoLED ECOdrive 1%, DALI 2, Logarithmic, DT6
ES3	eldoLED SOLOdrive 0.1%, DALI 2, Logarithmic, DT6

Lutron Drivers

LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
------------	---

How to specify Circuiting, Battery and Emergency

1

- Select fixture circuiting from options below
- Some VERBENA configurations will not accommodate all circuiting options, consult with factory

Circuiting

1	Single Circuit
E	Emergency Circuit only
N	Night Light Circuit only



- Battery and emergency options are available in addition to fixture circuit
- Select battery and emergency options below; factory shop drawing required
- Some VERBENA configurations will not accommodate all circuiting options, consult with factory
- Configurations with PLL or ILL or any Emergency control device will require standard remote box.

Battery and/or Emergency If Required


0 No battery or specific emergency required

Battery

- Battery is REMOTE
- Select battery type if required, indicate total QTY. *Example 2PLL*
- 90 minute battery runtime; test button is remote to fixture
- Battery operates full length of housing up to 8' on individual fixtures or within continuous row
- For more battery options available, see Pinnacle Resource Guide

0	No battery
_FSB	Factory Select Battery 10w, Integral Lithium
_FSBST	Factory Select Battery 10w, Integral Lithium Self Testing
_ILL	lota 10w, Integral Lithium, Self Testing
_IRC	lota 10w, Remote, Dual conduit flex
_PLL	Bodine 10w, Integral Lithium, Self Testing
_PRD	Bodine 10w, Remote, Dual conduit flex

Standard Remote Box



For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 92.3 (LPW) x 10 (watts) = 923 battery lumen output

Emergency

- Emergency Control Device REMOTE in driver box
- Select emergency section type if required, indicate total QTY. *Example 1E*
- Combine battery and emergency section ordering codes if both options are selected
- Emergency circuiting sections are for use when specifying emergency options on continuous runs

_FSG	Factory Select ALCR Emergency Control Device, UNV
_GI	lota ETS-DR, Emergency Control Device, UNV
_E	Emergency circuit
_N	Night Light circuit
_L	Life Safety circuit section NO THROUGH WIRE

Battery OR Emergency Ordering Examples

- Single circuit, 10w Integral Battery Ordering Code: 1-1PLL
- Emergency only, 10w Integral Battery Ordering Code: E-1PLL

Finish

- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

W	White (<i>white cord/white canopy</i>)
S	Metallic Silver (<i>white cord/silver canopy</i>)
BL	Textured Black (<i>black cord/black canopy</i>)
BR	Bronze (<i>white cord/bronze canopy</i>)
GR	Graphite (<i>white cord/graphite canopy</i>)
CC	Custom Color (<i>white cord/CC canopy to match fixture</i>)

Fixture Options

- Domestic content option - compliance is configuration dependent; consult factory for conformation

BA Buy America(n) Act and/or Build America Buy America Compliant

Controls


- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.



Photometrics


Satine Lens

Test #	KPL2015-2
Catalog #	V3D-A-N-40-4
Lumens	3868 Lm
Watts	27.5 W
Efficacy	141 LPW



Widespread Lens

Test #	KPL2015-1
Catalog #	V3I-N-WS-40-4
Lumens	3883 Lm
Watts	24.2 W
Efficacy	161 LPW



Candela Distribution

Vert Angle	Horizontal Angle	0	22.5	45	67.5	90
0		1117	1117	1117	1117	1117
5		1110	1114	1109	1109	1113
10		1110	1114	1109	1109	1113
15		1095	1099	1095	1096	1100
20		1095	1099	1095	1096	1100
25		1071	1074	1072	1073	1077
30		1071	1074	1072	1073	1077
35		1036	1041	1039	1042	1047
40		1036	1041	1039	1042	1047
45		994	999	998	1002	1007
50		994	999	998	1002	1007
55		942	947	949	953	960
60		942	947	949	953	960
65		884	889	892	897	905
70		884	889	892	897	905
75		818	822	828	837	843
80		818	822	828	837	843
85		747	750	757	770	778
90		747	750	757	770	778

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	14199	11327	10779
55	13556	10171	9731
65	12502	8940	9357
75	10627	8679	9572
85	8488	8857	9984

Candela Distribution


Vert Angle	Horizontal Angle	0	22.5	45	67.5	90
90		13	92	201	255	259
95		48	130	260	320	324
100		98	181	323	391	394
105		162	234	388	466	472
110		237	304	456	546	556
115		315	382	526	624	631
120		397	459	607	701	709
125		474	539	687	781	789
130		556	618	762	856	865
135		637	693	826	919	929
140		711	764	882	968	977
145		784	829	926	1002	1011
150		850	886	964	1024	1032
155		909	935	993	1037	1043
160		960	977	1015	1043	1048
165		999	1010	1031	1046	1050
170		1029	1032	1043	1048	1051
175		1046	1048	1050	1049	1051
180		1052	1052	1052	1052	1052

For all available IES files, please visit our website at pinnacle-ltg.com. Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP or IAS accredited testing laboratory. Testing conducted at 25°C ambient conditions



Multi Connector Layout

- Use the below to sketch your desired pattern. Available fixture and connectors are listed in the legend. Label your pattern components according to legend to simplify specification.
- Label the linear sections with length, and label the pattern with light direction, Direct (**D**) or Indirect (**I**) - entire pattern will be either direct or indirect, to change direction of light in pattern see V3AJ spec sheet.
- Cannot use connector with another connector.
- All lengths are TO THE FOOT ONLY.



A large grid for sketching the desired pattern layout. The grid is 20 units wide and 20 units high. Each unit is 1 foot by 1 foot. The grid is used to sketch the desired pattern layout using the connectors and lengths defined in the legend.



Applications & Certificates

Construction: 6063-T6 Extruded aluminum housing. Highly reflective die-formed white painted reflector.

Shielding: Diffuse snap-in acrylic lens with matte finish, removable for maintenance.

Mounting: Conductive Aircraft cable, wall and surface mount available. Power mount supplied with conductive aircraft cable and oval 6-1/2" H x 4-1/4" W canopy. Non-power supplied with aircraft cable and 2" (50.8mm) canopy. Refer to installation instructions for appropriate ceiling detail.

LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%; 2' or 3' lengths may have a greater wattage deviation. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 124,900 hours and L90 = 37,200 hours. MacAdam 3-Step Ellipses. Not all products are Lighting Facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

CRI, CCT & Output: Three lumen packages available. Low (LO), Medium (MO) and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 90 CRI = R9≥50.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL4 in Driver section when 347 volt (3) is selected. Some VERBENA configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver option is Factory Selected Driver 0-10V, 1% = FSD. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 107°F/42°C. For more driver options, see Pinnacle Resource Guide. Some VERBENA configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some VERBENA configurations will not accommodate all circuiting options; consult with factory.

Remote Mounting Guide

Distance limited by max input watts shown.

Max Distance	56' (.53A)	42' (.7A)	28' (1.05A)	20' (1.5A)	12' (2A)
4' Housing	4.0w/ft	5.4w/ft	8.2w/ft	11.9w/ft	16.1w/ft
8' Housing	N/A	2.6w/ft	4.0w/ft	5.8w/ft	7.8w/ft

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is remote to fixture. For more Battery options, see Pinnacle Resource Guide.

Finish: Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes. Contact factory for additional custom color and finish options.

Controls: Consult factory.

Buy America Act (BAA) and Build America, Buy America Act (BABA) Compliance: BAA and/or BABA compliance options are available to support federally funded projects requiring domestic content. Availability depends on configuration; Compliance is configuration-dependent; consult factory for confirmation.

Labels: UL and cUL 2108 Listed. Low, Medium and HO lumen packages are approved for dry/damp location unless otherwise noted.

Fixture Weight: Maximum fixture weight is 10 lbs for a standard 4' fixture.

Warranty: VERBENA offered with a 5-year limited warranty. Covers LED, driver and fixture.