


LINERO L6DI-A

Single Source Linear



Key Features

- One piece die-formed 18 gauge steel housing
- Highly reflective die-formed white painted steel reflector
- Die-cast aluminum end caps
- LINERO offered with a 5-year limited warranty that covers LED, driver and fixture
- UL and cUL Listed
- Approved for dry/damp location
- Room-Side Maintenance for LED system



QUICKSHIP



Example Part #: L6DI-A-70-835HO-26'-AC48G1-U-OL2-1-0-W

L6DI-A

HOUSING - DISTRIBUTION - CRI, CCT & OUTPUT - LENGTH - MOUNTING - VOLTAGE - DRIVER - CIRCUITING - BATTERY & EMERGENCY - FINISH - FIXTURE OPTIONS - CONTROLS


L6DI-A	---	-----	-----
HOUSING	DISTRIBUTION	CRI, CCT & OUTPUT <i>QS</i> ¹	LENGTH ²
L6DI-A - LINERO 6 with Satine Lens <i>QS</i> <i>Shielding pg. 2</i>	40 - 40% Direct / 60% Indirect <i>QS</i> 70 - 70% Direct / 30% Indirect <i>QS</i> 100 - 100% Direct <i>QS</i> <i>Shielding pg. 2</i>	_27_ - 2700K _30_ - 3000K _35_ - 3500K _40_ - 4000K CL - Custom Lumens CW - Custom Watts <i>Lumen Output pg. 2-4</i>	_ - Individual Fixture <i>QS</i> _ - Continuous Row <i>QS</i> <i>Length pg. 5</i>
MOUNTING ³	VOLTAGE	DRIVER	CIRCUITING
AC_G - AC to Grid <i>QS</i> AC_JB - AC to J Box <i>QS</i> AC_ST - AC to Structure <i>QS</i> AC5_G - 5" Non-Power Canopy AC5_JB - 5" Non-Power Canopy SQ_G - 5" Square Canopy SQ_JB - 5" Square Canopy WA - Wall Mount <i>Mounting pg. 5</i>	U - Universal <i>QS</i> <i>(120 thru 277V)</i> 1 - 120V <i>QS</i> 2 - 277V <i>QS</i> 3 - 347V <i>Voltage pg. 5</i>	FSD - Factory Select Driver (1%, 0-10v) <i>QS</i> PL2 - Advance Xitanium (0-10v, 1%) OL2 - eldoLED Optotronic (1%, 0-10v) EE1 - eldoLED ECOdrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0.1%, 0-10v) OL5 - eldoLED Optotronic (1%, 0-10v, AUX) OD1 - eldoLED Optotronic (1%, 0-10v, DEXAL) LH1 - Lutron Hi-lume (1%, EcoSystem) <i>Driver pg. 6</i>	1 - Single Circuit <i>QS</i> M - Multi Circuit E - Emergency <i>QS</i> <i>(entire fixture)</i> N - Night Light <i>QS</i> <i>(entire fixture)</i> <i>Circuiting pg. 6</i>
BATTERY & EMERGENCY ⁴	FINISH	FIXTURE OPTIONS ^{5,6}	CONTROLS ⁷
0 - None <i>QS</i> _FSB - Factory Select Battery <i>QS</i> _FSG - Factory Select ALCR _GI - Iota ETS DR _GB - Bodine GTD _ILL - Iota 10w _PLL - Bodine 10w _E - Emergency circuit section _N - Night Light circuit section _L - Life Safety circuit section <i>Battery and Emergency pg. 6-7</i>	W - White <i>QS</i> S - Metallic Silver BR - Textured Black BR - Bronze GR - Graphite CC - Custom Color <i>Finish pg. 7</i>	QS - QuickShip <i>QS</i> DSP - Customer Supplied Battery/Driver/ Sensor BA - Buy America(n) Act and/or Build America Buy America Compliant <i>Fixture Options pg. 7</i>	DLMFC - Wattstopper DLM EASYS - Philips EasySense SNSLM - Wattstopper PLUS SensiLUM WVLX - Eaton WaveLinX VDO - Lutron Vive Sensor VRF - Lutron Vive Connected <i>Controls pg. 7</i>

¹When specifying SOURCE the first _ is for specifying either 8 - 80CRI, 9 - 90CRI. The ending _ _ are for specifying output, example **HO** - High Output. See output charts for more information. ²Individual fixtures come in 4', 6' & 8' lengths. Continuous rows available in 2' increments, starting at 4'. ³Specify AC Cable length, standard AC is 48"; Specify grid: G1=15/16", G9=9/16", GS=Screw Slot. Example AC48G1. ⁴Enter quantity for Battery and Emergency, Example 2PLL. ⁵QS must be used in fixture options section of part number to qualify. 1/8" increments not available for QS. ⁶Compliance is configuration dependent; consult factory for confirmation. ⁷Controls can only be used with Single Circuit (1) or Emergency Circuit (E). See Controls chart on page 6 for driver options and more information.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Distribution



40% Direct Source: Static White

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory
- 90 CRI = R9≥50

Custom Output- Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL835950)	<i>Specify lumens between standard offering listed below. Lumens are specified per color temp</i>
CW _____	Specify CRI, CCT and desired wattage (i.e. CW9409.5)	<i>Specify watts between standard offering listed below</i>

80 CRI

	Color	Lumens <i>per foot</i>	Shielding	
			A Satine Watts/ft	LPW
830LO	3000K	400	2.8	144.7
830	3000K	600	4.0	150.4
830HO	3000K	850	5.7	149.1
830VHO	3000K	1250	8.4	148.7
835LO	3500K	400	2.7	149.7
835	3500K	600	3.9	155.7
835HO	3500K	850	5.5	154.4
835VHO	3500K	1250	8.1	154.0
840LO	4000K	400	2.7	150.4
840	4000K	600	3.8	156.3
840HO	4000K	850	5.5	155.1
840VHO	4000K	1250	8.1	154.7

90 CRI

927LO	2700K	400	3.4	118.3
927	2700K	600	4.9	125.2
927HO	2700K	850	6.8	125.3
927VHO	2700K	1250	10.1	123.4
930LO	3000K	400	3.3	121.1
930	3000K	600	4.6	129.4
930HO	3000K	850	6.6	129.6
930VHO	3000K	1250	9.8	127.7
935LO	3500K	400	3.2	123.7
935	3500K	600	4.5	132.2
935HO	3500K	850	6.4	132.4
935VHO	3500K	1250	9.6	130.5
940LO	4000K	400	3.3	122.8
940	4000K	600	4.6	131.2
940HO	4000K	850	6.5	131.4
940VHO	4000K	1250	9.7	129.5

¹LPW and watts/ft based off 96" fixture size.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



70% Direct Source: Static White¹

Custom Output- Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL835950)	<i>Specify lumens between standard offering listed below. Lumens are specified per color temp</i>
CW _____	Specify CRI, CCT and desired wattage (i.e. CW9409.5)	<i>Specify watts between standard offering listed below</i>

80 CRI

	Color	Lumens <i>per foot</i>	Shielding A	
			Satine <i>Watts/ft</i>	<i>LPW</i>
830LO	3000K	400	3.6	111.6
830	3000K	600	5.4	111.7
830HO	3000K	850	7.6	111.6
830VHO	3000K	1250	11.6	108.1
835LO	3500K	400	3.5	115.5
835	3500K	600	5.2	115.7
835HO	3500K	850	7.4	115.6
835VHO	3500K	1250	11.2	112.1
840LO	4000K	400	3.4	116.0
840	4000K	600	5.2	116.0
840HO	4000K	850	7.3	116.1
840VHO	4000K	1250	11.1	112.6

90 CRI

927LO	2700K	400	4.3	93.8
927	2700K	600	6.4	93.9
927HO	2700K	850	9.2	92.7
927VHO	2700K	1250	13.8	90.5
930LO	3000K	400	4.1	97.0
930	3000K	600	6.2	96.8
930HO	3000K	850	8.9	95.9
930VHO	3000K	1250	13.3	93.7
935LO	3500K	400	4.0	99.3
935	3500K	600	6.1	98.9
935HO	3500K	850	8.7	98.0
935VHO	3500K	1250	13.1	95.8
940LO	4000K	400	4.1	98.4
940	4000K	600	6.1	98.2
940HO	4000K	850	8.7	97.3
940VHO	4000K	1250	13.2	95.0

¹LPW and watts/ft based off 96" fixture size.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



100% Direct Output

Custom Output- Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL835950)	<i>Specify lumens between standard offering listed below. Lumens are specified per color temp</i>
CW _____	Specify CRI, CCT and desired wattage (i.e. CW9409.5)	<i>Specify watts between standard offering listed below</i>

80 CRI

	Color	Lumens <i>per foot</i>	Shielding A	
			Satine <i>Watts/ft</i>	LPW
830LO	3000K	400	3.6	111.1
830	3000K	600	5.4	111.2
830HO	3000K	850	7.6	111.1
830VHO	3000K	1250	11.6	107.6
835LO	3500K	400	3.5	115.0
835	3500K	600	5.2	115.1
835HO	3500K	850	7.4	115.1
835VHO	3500K	1250	11.2	111.6
840LO	4000K	400	3.5	115.5
840	4000K	600	5.2	115.6
840HO	4000K	850	7.4	115.6
840VHO	4000K	1250	11.2	112.0

90 CRI

927LO	2700K	400	4.3	93.4
927	2700K	600	6.4	93.4
927HO	2700K	850	9.2	92.3
927VHO	2700K	1250	13.9	90.0
930LO	3000K	400	4.1	96.6
930	3000K	600	6.2	96.3
930HO	3000K	850	8.9	95.5
930VHO	3000K	1250	13.4	93.2
935LO	3500K	400	4.0	98.8
935	3500K	600	6.1	98.4
935HO	3500K	850	8.7	97.6
935VHO	3500K	1250	13.1	95.3
940LO	4000K	400	4.1	97.9
940	4000K	600	6.1	97.7
940HO	4000K	850	8.8	96.9
940VHO	4000K	1250	13.2	94.6

¹LPW and watts/ft based off 96" fixture size.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Length


- All individual units cannot be joined, end caps are factory installed and cannot be removed
- Add 3/8" for each end cap or 3/4" to the overall length of the row
- Aperture sizes vary, 4' fixtures have a single 45-7/16" long aperture, 6' fixtures have two 33-11/16" long apertures, and 8' fixtures have two 45-7/16" long apertures

4	6	8	—
Individual Fixture	Individual Fixture	Individual Fixture	Continuous Run
48" (1,219mm)	72" (1,829mm)	96" (2,438mm)	Continuous rows available in 2' increments, starting at 4'
			Specify to the 2', starting at 4' >>>

Mounting

- Specify cable length in ordering code (AC48G1)
- Standard adjustable cable. Specify 48", 120", 240" or 350"
- Adjustable aircraft cable mounts on 4'-0" (1,219mm), 6'-0" (1,829mm) or 8'-0" (3438.4mm) center
- End caps and standard white power cord attached at factory
- Aircraft Cable supplied with 5" (127mm) power and 2" (51mm) non-power canopies
- Canopies match fixture finish, power cords are white or black depending on fixture finish. See Finish section for additional details.
- Approved for dry/damp location unless otherwise noted
- Refer to installation instructions during installation at the job site
- Maximum fixture weight is 17 lbs. per 4' fixture

AC_G1	Adjustable AC to 1" (15/16") T-Bar
AC_G9	Adjustable AC to 9/16" T-Bar
AC_GS	Adjustable AC to Screw Slot T-Bar
AC_JB	Adjustable AC to Junction Box
AC_ST	Adjustable AC to Structure
AC5_G	5" (127mm) Non-Power Canopy
AC5_JB	5" (127mm) Non-Power Canopy
SQ_G	5" (127mm) Square Canopy
SQ_JB	5" (127mm) Square Canopy
WA	Wall Mount



Voltage

- Some LINERO configurations will not accommodate all voltage options; consult with factory

U	Universal
1	120 volt
2	277 volt
3	347 volt



Driver

- Standard Driver Option = FSD
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more driver options see Pinnacle Resource Guide
- Some LINERO configurations will not accommodate all driver options; consult with factory

0-10V Drivers

FSD	Factory Select Driver 1%, 0-10v
PL2	Signify Advance Xitanium 1%, 0-10v
PL4	Advance Xitanium 347v 1%, 0-10v, requires 347v
OL2	eldoLED Optotronic, 1%, 0-10v
OL4	eldoLED Optotronic 347v, 1% 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0-10v, 0.1% Logarithmic
ES2	eldoLED SOLOdrive 0-10v, 0% Linear
PL5	Advance Xitanium 1%, 0-10v, AUX, Dim to Off
OL5	eldoLED Optotronic 1%, 0-10v, AUX

DALI Drivers

EE3	eldoLED ECOdrive 1%, DALI 2, Logarithmic, DT6
ES3	eldoLED SOLOdrive 0.1%, DALI 2, Logarithmic, DT6
OD1	eldoLED Optotronic 1%, DEXAL, DALI 2, DT6, Self powered link
EE4	eldoLED ECOdrive 1%, DALI 2, Linear, DT6
ES4	eldoLED SOLOdrive 0.1%, DALI 2, Linear, DT6
PR1	Advance Xitanium SR, DALI 2, Self powered link

Lutron Drivers

LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
------------	---

Alternate Drivers

PS1	Advance Xitanium Step Dimming 50%/100%
EH1	ERP 1%, Line Voltage and ELV, requires 120v

How to specify Circuiting, Battery and Emergency

- Select fixture circuiting from options below
 - Some LINERO configurations will not accommodate all circuiting options, consult with factory

Circuiting

1	Single Circuit
M	Multi Circuit
E	Emergency Circuit only
N	Night Light Circuit only

- Battery and emergency section options are available in addition to fixture circuit
 - Select battery and emergency section options below; factory shop drawing required
 - Some LINERO configurations will not accommodate all circuiting options, consult with factory

Battery and/or Emergency If Required

0 No battery or specific emergency section required

Battery

- Select battery section type if required, indicate total QTY. *Example 2PLL*
- 90 minute battery runtime; test button is integral to fixture
- For more battery options available, see Pinnacle Resource Guide

0	No Battery
_FSB	Factory Select Battery (10w option)
_FSBST	Factory Select Battery (10w, Self Testing)
_ILL	Iota 10w Integral Lithium, Self Testing
_PLL	Bodine 10w Integral Lithium, Self Testing

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- $92.3 \text{ (LPW)} \times 10 \text{ (watts)} = 923 \text{ battery lumen output}$



Emergency

- Select emergency section type if required, indicate total QTY. *Example 1E*
- Combine battery and emergency section ordering codes if both options are selected

_FSG	Factory Select ALCR Emergency Control Device, UNV
_GI	Iota ETS-DR, Emergency Control Device, UNV
_GB	Bodine GTD, Emergency Control Device, 120v or 277V
_E	Emergency circuit section
_N	Night Light circuit section
_L	Life Safety circuit section NO THROUGH WIRE

Battery OR Emergency Ordering Examples

- Single circuit, 10w Integral Battery Ordering Code: 1-1FSB
- Emergency only, 10w Integral Battery Ordering Code: E-1PLL
- Single circuit, GTD required Ordering Code: 1-1GB

Finish

- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

W	White (<i>white cord/white canopy</i>)
S	Metallic Silver (<i>white cord/silver canopy</i>)
BL	Textured Black (<i>black cord/black canopy</i>)
BR	Bronze (<i>white cord/bronze canopy</i>)
GR	Graphite (<i>white cord/graphite canopy</i>)
CC	Custom Color (<i>white cord/color match canopy</i>)

Fixture Options

- Additional options to enhance the fixture and finish of the product

QS	Quick Ship
DSP	Customer Supplied Battery/Driver/Sensor

- Domestic content option - compliance is configuration dependent; consult factory for conformation

BA	Buy America(n) Act and/or Build America Buy America Compliant
-----------	---

Quick Ship

Distribution	CRI, CCT & Output	Mounting	Voltage	Driver	Circuiting	Battery	Finish		
10-Day									
40	40% Direct	80 CRI, All color temperatures, all lumen packages Including custom See pg 2-3	AC__GX	Grid	U Universal <i>(120 thru 277)</i> 1 120 V 2 277V	FSD Factory Select Driver <i>(1%, 0-10v)</i>	1 Single Circuit E Emergency N Night Light	0 None FSB Factory Select Batter	W White
70	70% Direct		AC__JB	Junction Box					
100	100% Direct		AC__ST	Structure					

All lengths and continuous rows up to 1,000 ft OR 150 individual fixtures. Consult factory for larger projects.

Controls

- Pinnacle Lighting offers easy to specify network control solutions that connect to an intelligent centralized system to maximize lighting energy efficiencies or integral sensors for individual fixture control
- Pinnacle Lighting fixtures ship technology ready; commissioning by others
- Controls can only be used with Single Circuit (1) or Emergency Circuit (E)
- Contact factory for any non-standard configurations for layout, placement, or EM options
- One drop per sensor typical, consult factory for more information

	Solution	Components	Network/Sensor	Connection	Required Drivers	Limitations
DLMFC	Legrand Wattstopper DLM	LMFC-011	Digital Lighting Management (DLM)	Wired, one RJ45 ports	OL2, OL4	None
EASYS	Philips EasySense	SNS-210	Daylight/PIR Occupancy	Wireless to switches	PR1	Not available with 347 volt
SNSLM	Wattstopper PLUS SensiLUM	EN-CLM-PIR-DD-ZB	Encelium, Daylight/PIR Occupancy	Wireless	OD1, OL5	Not available with 347 volt
WLWX	Eaton WaveLinx	SWPD1, MSP3IVMVDC1	WaveLinx WCL, Daylight	Wireless	Any 0-10v	Not available with 347 volt
VDO	Lutron Vive Sensor	DFCSJ-OEM-OCC	Vive, Daylight/PIR Occupancy	Wireless	OD1, PR1	Not available with 347 volt
VRF	Lutron Vive Connected	DFCSJ-OEM-RF	Vive	Wireless	OD1, PR1	Not available with 347 volt

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568


L6DI_LED_SPEC_FEBRUARY2026



Photometrics


Satine Lens

Test # ITL93486-GONIOPHOTOMETRY
 Catalog # L6DI-A-40-840VHO-4
 Lumens 5567 lm
 Watts 36.7 W
 Efficacy 151.7 LPW




Satine Lens

Test # ITL90506-GONIOPHOTOMETRY
 Catalog # L6DI-A-70-840VHO-4
 Lumens 4865 lm
 Watts 43 W
 Efficacy 113.1 LPW



Satine Lens

Test # ITL90505-GONIOPHOTOMETRY
 Catalog # L6D-A-100-840VHO-4
 Lumens 4504 lm
 Watts 39.8 W
 Efficacy 113.2 LPW



Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	733	733	733	733	733
5	731	732	734	736	737
15	717	720	740	757	760
25	683	691	735	771	783
35	621	637	697	745	762
45	532	553	614	661	678
55	419	437	485	523	539
65	288	300	330	355	364
75	149	156	169	180	186
85	32	34	36	37	39
90	0	0	0	0	0
95	74	73	74	76	78
105	199	206	258	315	321
115	297	337	535	688	700
125	376	444	713	924	965
135	448	513	754	981	1048
145	514	558	721	907	976
155	573	592	670	763	805
165	615	618	641	665	675
175	638	638	640	641	642
180	641	641	641	641	641

Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	1077	1077	1077	1077	1077
5	1073	1074	1074	1075	1076
15	1043	1040	1054	1063	1063
25	975	972	1001	1021	1027
35	869	872	910	937	946
45	731	738	774	802	813
55	566	573	603	625	632
65	386	391	408	423	430
75	200	203	211	217	219
85	45	46	47	49	48
90	0	0	0	0	0
95	12	15	13	13	13
105	62	65	67	67	70
115	165	173	185	191	200
125	268	306	356	386	399
135	336	392	470	520	537
145	375	426	513	567	586
155	393	423	497	543	559
165	394	404	441	471	482
175	389	389	392	397	398
180	388	388	388	388	388

Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	1606	1606	1606	1606	1606
5	1599	1598	1599	1599	1600
15	1541	1532	1547	1554	1552
25	1418	1410	1436	1453	1454
35	1241	1241	1274	1296	1301
45	1027	1030	1063	1086	1095
55	786	791	816	835	845
65	530	534	549	564	570
75	273	275	281	288	292
85	61	61	62	63	62
90	0	0	0	0	0

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	7336	8467	9349
55	7123	8245	9163
65	6645	7614	8398
75	5613	6367	7007
85	3580	4028	4363

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	10368	10978	11531
55	9897	10544	11051
65	9160	9682	10204
75	7750	8176	8486
85	5178	5408	5523

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	11079	11467	11812
55	10453	10852	11237
65	9566	9909	10288
75	8046	8281	8606
85	5339	5426	5426

For all available IES files, please visit our website at pinnacle-ltg.com. Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP or IAS accredited testing laboratory. Testing conducted at 25°C ambient conditions

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Approvals & Certifications

Construction: One piece die-formed 18 gauge steel housing in a 6-7/8" (174mm) by 1-11/16" (42mm) profile with a 1-3/8" (34mm) side profile. Standard 4'-0" (1,219mm), 6'-0" (1,828mm) and 8'-0" (3,438mm) fixtures can be joined to create continuous runs. Standard high reflectance die-formed white painted aluminum.

Shielding: Direct: white satine lens with matte finish. Indirect: 40/60 distribution uses a batwing diffuser, 70/30 distribution uses a perforated reflector and clear dust guard, 100 direct distribution uses a steel top cover. 4' fixtures have a single 45-7/16" long aperture, 6' fixtures have two 33-11/16" long apertures, and 8' fixtures have two 45-7/16" long apertures.

Mounting: Adjustable aircraft cable, or wall mounts available. Air Craft Cable mounts on 4'-0" (1,219mm), 6'-0" (1,828mm) and 8'-0" (3,438mm) centers. Refer to installation instructions for appropriate ceiling detail.

LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. Luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. Lifetime Projection for 40%, 70% and 100%: L70 lifetime - 130,000 hours and L90 lifetime - 39,000 hours. MacAdam 3-Step Ellipses. For all available IES files, please visit our website at pinnacle-ltg.com.

CRI, CCT & Lumen Output: Two lumen packages available. Standard and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 90 CRI = R9≥50. Fixture performance and photometric data based on 8' configuration for worst case input voltage. Published lumen or wattage data based on OL1 configuration.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL4 in Driver section when 347 volt (3) is selected. Some LINERO configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Factory Select Driver 0-10V, 1% = FSD. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range for 40%, 70% and 100%: -23F/-30C to 125F/52C For more driver options, see Pinnacle Resource Guide. Some LINERO configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Multi circuit (M), Emergency circuit (E), Night Light circuit (N) or Life Safety (L). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some LINERO configurations will not accommodate all circuiting options; consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is integral to fixture. For more Battery options, see Pinnacle Resource Guide.

Finish: Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish, consult factory for chip of standard paint finishes. Canopies painted white unless specified differently in the options section of the part number. Contact factory for additional custom color and finish options.

Controls: Standard options available, refer to Controls section table for available options, component part number(s), connection type, required driver and limitations. Mod options available, consult with factory.

Buy America Act (BAA) and Build America, Buy America Act (BABA) Compliance: BAA and/or BABA compliance options are available to support federally funded projects requiring domestic content. Availability depends on configuration; Compliance is configuration-dependent; consult factory for confirmation.

Labels: UL and cUL 1598 listed. Approved for dry/damp location unless otherwise noted.

Fixture Weight: Maximum fixture weight is 17 lbs (per 4' fixture).

Warranty: LINERO LED offered with a 5-year limited warranty. Covers LED, driver and fixture.